

Tiered Display With Lockable Shutter

SD75-190-SHU


**MIRROR
FINISH
STAINLESS
STEEL**

SD75-130-SHU



FEATURES

Mirror finish 304 grade stainless steel exterior & interior

4 adjustable heavy duty shelves (350mm deep)

Adjustable feet

Integral lockable roller shutter

Internal illumination

Clear acrylic shelf edge risers

Condensing unit pull out for easy maintenance

TECHNICAL SPECIFICATIONS

Controller: Digital controller with temperature display

Cooling: Ventilated

Defrost: Automatic

Refrigerant: R290

Climate Class: 3

Temperature Range: +2°C ~ +5°C

Power Supply: 13amp (SD75-100, 130)
2x 13amp (SD75-190, 250)

MODEL	FINISH	EXT. DIMENSIONS (H x W x D mm)	POWER CONSUMPTION (incl. 750W drip tray)	DECIBELS	WEIGHT (kg)	RRP
SD75-100-SHU	Mirror finish 304 grade stainless steel exterior & interior	1950 x 1000 x 750	1365W (2115W)	65dBA	251	
SD75-130-SHU		1950 x 1300 x 750	1404W (2154W)	68dBA	291	
SD75-190-SHU		1950 x 1900 x 750	2652W (3402W)	65dBA	410	
SD75-250-SHU		1950 x 2500 x 750	2808W (4308W)	65dBA	480	



Optional snack baskets
- See page 339