



Wall Mounted Automatic Water Boiler

M3F, M5F, M7F

- High quality boiling water on tap 24 hours a day
- Wall mounted, compact design
- Easy installation – UK 3 pin plug and three screws
- Built-in water filtration system improves water quality
- High volume, easy change FilterFlow cartridge
- Adjustable water temperature – from 70°C – 96°C
- Precise electronic temperature control system
- LCD information panel
- Enhanced multi-level diagnostics



Water Boiler Features

- High quality filtered boiling water on tap 24 hours a day
- LCD information panel
- Precise electronic temperature control system
- Insulated tank for minimal heat loss and energy conservation
- High volume, easy change FilterFlow cartridge - removes sediment and impurities such as chlorine
- Adjustable water temperature - from 70°C - 96°C
- Enhanced multi-level diagnostics
- Designed for connection to a potable cold water supply
- WRAS approval pending

Cleaning and Servicing

- Easy clean stainless steel external finish
- Easy change filter cartridge

Overall Construction

- Long life incoloy element
- Brushed finish stainless steel
- Stainless steel water tank
- 1.5 metre cable and a 13 amp moulded plug

Inclusive Accessories

- Water feed hose (1m)
- FC04 5,600 litre filter cartridge
- Wall mounting bracket

Available Options

Available Accessories

- FC04 5,600 litre replacement filter cartridge
- DP10 Descaler powder
- DR94 M3F drip tray
- DR95 M5F & M7F drip tray



Technical Data

	M3F	M5F	M7F
Width (mm)	300	340	340
Depth (mm)	203	203	203
Depth (mm) inc tap	269	269	269
Height (mm)	398	448	563
Output per hour (litres)	28	28	28
Rapid Draw-off (litres)	3.5	5.5	8
Heat up time to working temperature (full tank capacity)	8	12	18
Water inlet connection (BSP male)	3/4"	3/4"	3/4"
Water inlet pressure (bar)	1 to 8	1 to 8	1 to 8
Total power rating (kW)	3	3	3
Standby power consumption (kW)	0.6	0.6	0.6
Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps)	13	13	13
Net weight empty (kg)	8.9	9.9	11.6
Net weight full (kg)	12.1	15.1	19.4
IPX Protection	IPX23	IPX23	IPX23

