



British Manufacturing
since 1957



The Professionals Choice

UCB47T

InstaTap Under Counter Hot Water Boiler with Twin Fonts



FULL SPECIFICATION



UCB47T InstaTap Under Counter Hot Water Boiler with Twin Fonts

Type	Under-counter range – Push-button Dispenser (twin fonts)
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
Capacity (Litres)	47
Unit dimensions (W x D x H) mm	465 x 500 x 560
Packed dimensions (W x D x H) mm	590 x 600 x 1045
Product weight (c/w dispense font) empty (kg)	27.5
Product weight (c/w dispense font) full (kg)	68.0
Packed weight (c/w dispense font) (kg)	40.5
CONSTRUCTION (UC unit):	
Outer fabrication (body) construction	304 grade Stainless Steel
Tank construction	304 & 316 grade Stainless Steel
DISPENSE FONT(S):	
Two x Dispense Fonts: dimensions (W x D x H) mm	185 x 185 x 225 (standard font)
Tap font clearance (standard height font) mm	150 (tall font option available with clearance of 250mm)
Dispense font construction:	304 grade Stainless Steel & chrome-plated Aluminium
Font interface with UC unit (electrical & water)	1.2 metre, plug-in XLR lead (electrical) and silicone rubber water transfer tube (water)
ELECTRICAL:	
Power rating (kW)	4.5 (or can be configured as 6.75kW)
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (20A or 30A)
Electrical Installation	Wire to 30amp (6.75kW) or 20amp (4.5kW) single-phase supply via an isolation switch
Fitted cable length (m)	1.7m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4" BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	15mm push-fit (right-side of UC unit)
PERFORMANCE:	
Water temperature delivered	90°C (default for stadiums) – adjustable between 80°C & 95°C
Heat up time to working temperature	40 mins (@ 6.75kW) or 63 mins (@ 4.5kW)
Output per hour (@ default temperature setting)	63 Litres (@ 6.75kW) or 44 Litres (@ 4.5kW)
Rapid draw-off	47 Litres
Recovery per minute	1.2 Litres (6.75kW) or 0.7 Litres (@ 4.5kW)
Stand-by power loss (idle mode)	0.12 kW/h
FILTRATION:	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	
Unique automatic recirculating mode [to prevent under temperature drinks]	Yes (circulation delay is programmable; between 1 & 200 minutes)
Choice of measured water delivery or on-demand setting	Yes
Energy saving ECO mode	Yes
Tank-baffle plates – unique design aids heat recovery & reduces steam emissions to atmosphere	Yes
Early warning lime-scale diagnostics (5 sensors)	Yes - advanced
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	
WRAS approved	Yes
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes (self-certified) - BS EN 60335-1 & 2
WARRANTY & AFTER-SALES:	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

Instanta Limited

T: 01704 501114 F: 01704 501115 E: sales@instanta.com



Certificate Numbers: FM01234 & EM01234