Speed Queen®

SWN & SDE/SDG



DRYER

- Front loading for easy loading and unloading
- Door is reversible and upfront lint filter is easy to clean and secure
- Galvanized cylinder with gentle tumble to minimize wrinkles
- Coin or token operated

WASHER

- Electric Control Timer for reliable operation
- Stainless steel washtub and galvanized steel cabinet
- Spray rinse cycle
- Coin or token operated

Speed Queen®

SWN & SDE/SDG

MODEL	SWN	SDE/SDG
Basket/Cylinder Volume (litres)	79 L	198 L
Width (mm)	651mm	683mm
Depth (mm)	711mm	711mm
Height (mm) *	1092mm	1092mm
Work Surface Height (mm)	914mm	914mm
Weight – kg (lb)	86kg (190lb)	Electric: 61kg (135lb)
		Gas: 64kg (140lb)
Shipping Weight – kg (lb)	95kg (210lb)	Electric: 66kg (145lb)
		Gas: 68kg (150lb)
Cycle Time – minutes	16 – 31	Variable
Motor HP (Capacitor Start and Thermal Protected)	½ HP, 1 – speed	1/3 HP, 5.5 amps
Water Pressure – bar	Pressure fill – 1.4 / 8.3	N/A
Spin Speed - RPM	710	N/A
Cycle / Temperature	Hot	High
	Warm	Medium
	Cold	Low
		Delicate
Electrical Requirements	240v / 50Hz / 1ph – 13amp	Electric: 240v / 50Hz / 1ph – 32amp
		Gas: 240v / 50Hz / 1ph – 13amp
Electrically Heated	N/A	5.2 Kw
Gas Rate (BTU)	N/A	25,000 BTU
Type of Gas (Gas model only)	N/A	Factory-equipped natural/mixed gas. Convertible to LPG **
Utility Connections (mm)	N/A	Gas: 9.5 NPT
Air Outlet Diameter (mm)	N/A	102mm
Exhaust Airflow*** – litres/sec (cfm)	N/A	105 (220)
Maximum Exhaust Static Back Pressure	N/A	0.6"W.C.
Self-Adjusting Rear Legs	Yes	No
Available Colours	White	White
Top and Lid Finish	Porcelain	Porcelain
Approvals	CE	CE

^{*} Heights may vary slightly depending on levelling adjustments.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.



Head Office: Ampere Road, Newbury,

Berkshire RG14 2AE

 Sales:
 +44 (0)1635 263410

 Parts:
 +44 (0)1635 263412

 Service:
 +44 (0)1635 33881

 Switchboard:
 +44 (0)1635 33881

Fax: +44 (0)1635 32434

Email: enquiries@armstronglaundry.com
Web: www.armstronglaundry.com

Scottish office

5 Kelvin Gate, Kelvin Avenue, Hillington Park, Glasgow G52 4GA

Tel: +44 (0)141 892 2390 **Fax:** +44 (0)141 892 2387

Email: scotland@armstronglaundry.com



0.16

^{**} IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

^{***} Measured at point of exit from dryer.