

## Atosa WDG186HF Refrigerated Square Fronted Showcase with Rear Sliding Door Access



The Atosa WDG186HF offers a fantastic option to showcase your products in a refrigerated display. With sliding door easy access, it offers a great opportunity to present your goods in an aesthetically pleasing manner.

- ✓ Stainless Steel Interior Structure
- ✓ LED Interior Lighting
- ✓ Double Safety Glass at Front
- ✓ Automatic Defrost
- ✓ Climate Class 3
- ✓ Adjustable Feet
- ✓ Sliding Glass Rear Door
- ✓ Single Safety Glass at Back
- ✓ 3 Glass Shelves
- ✓ Interior Temp +2°C to +8°C

### SPECIFICATIONS

| Summary           |                         | Power and Performance          |              |
|-------------------|-------------------------|--------------------------------|--------------|
| Brand             | Atosa                   | Voltage (V/HZ/PH)              | 220-240/50/1 |
| Model             | WDG186HF                | Power (Watts)                  | 630          |
| Shelf Quantity    | 3 Shelves + Base        | Electrical Current (Amps)      | 3.3          |
| Material External | Stainless-Steel / Glass | 24Hrs Energy Consumption (kWh) | 10.75        |
| Material Internal | Stainless-Steel / Glass | Annual Consumption kWh/Year    | 3924         |
| LED Lights        | LED Strips              |                                |              |

| Key Specifications        |                   | Weights and Dimensions             |                                  |
|---------------------------|-------------------|------------------------------------|----------------------------------|
| Thermostat                | Carel / Dixell    | Exterior Dimension (WxDxH) mm      | 1800 x 660 x 1350                |
| Climate Class             | 3                 | Interior Dimension (WxDxH) mm      | 1710 x 540 x 760                 |
| Energy Efficiency Class   | C                 | Packaging Dimension (WxDxH) mm     | 1888 x 743 x 1400                |
| Defrost Method            | Air Defrost       | Shelf Dimensions mm                | x1 (1628 x 330), x2 (1628 x 280) |
| Refrigerant Type / Amount | R290/110 g        | Loading Capacity Per Shelf (kg pc) | 15                               |
| Inner Temperature (°C)    | +2° to +8°        | Net Weight (kg)                    | 217                              |
| Cooling Method            | Ventilated        | Gross Weight (kg)                  | 256                              |
| Foaming Material          | C5H10             |                                    |                                  |
| Castors                   | 4 (Braked)        |                                    |                                  |
| Gross Capacity (Litre)    | 678               |                                    |                                  |
| Insulation                | Polyurethane Foam |                                    |                                  |

