



Product Code: FMPRO1800RF 19-108

1800mm Pro multideck with rollershutter



Features & Benefits

- Five display levels maximising capacity
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (450mm) delivers increased volume compared to competitor cabinets
- Supplied on roller castors as standard for ease of positioning
- Add 20mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall-sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Robust lockable security roller shutter with full solid end panels
- Fully removable shelves and supports for ease of cleaning.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

External Finish

304 s/s Standard

Electrical, Service & Ecodesign Data

230/50/1 Standard

Fuse Required (A) 13

Internal Finish

304 s/s Standard

Specification

Width 1795

Height 1995

Depth 775

Weight (Unpacked, kg) 330

Weight (Packed, kg) 360.89

Depth Note Add 60mm to depth for spacer if product is to be wall-sited required for air circulation - detachable if not wall-sited

Noise dBA @ 1m 78.65

Refrigeration

R404a - Industry Standard Standard

Integral Refrigeration System Standard

Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced - see UK price list for conditions



Energy



Quality



Value



Design



Hygiene



After Care