

TUC-24F-HC

 Undercounter Foodservice Freezer, 1 Solid Swing Door



Dimensions		Build		Technical	
External Width (mm)	610	Door Description	1 Solid Swing Door	Temperature Range	-23°C
External Depth (mm)	627	Door Opening	Right (standard) or Left Field Reversible	Refrigerant	R290
External Height (mm)	802	Exterior Construction	Stainless steel front & countertop, aluminium sides & rear	Voltage/Frequency/Phase	220-240V/50-60Hz/1
Exclusions	Depth does not include 26 mm for rear bumpers.	Interior Construction	Clear coated aluminium, stainless steel base	Amps	1.6
Net Volume (Litres)	94	Air Intake Position	Front	Watts	368
Gross Volume (Litres)	158	Ventilation Position	Front	Climate Class	5
Supplied Shelves	2	Clearance Required	Zero back and sides	Operating Statement	Heavy Duty: This appliance is intended for use in ambient temperatures up to 40°C.
Shelf Size (L x D mm)	One 508 x 352 + One 508 x 273	Cord Length (Meters)	2.13	Test Standard	EN 16825
Internal Net Height (mm)	600	Standard w/ Locks	Standard	EEC	C
Unpackaged Weight (kg)	64			Energy Efficiency Index	44.4
Packaged Weight (kg)	75			Defrost Type	Auto
Packaged Dimensions (W x D x H mm)	788 x 762 x 1042			Energy Consumption (kWh/24h)	3.56
Supplied with	Built-in recessed castors (7mm clearance)			Energy Consumption (kWh/Annum)	1300



Specifications subject to change without notice.

Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia


0800 783 2049
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



TUC-24F-HC

 Undercounter Foodservice Freezer, 1 Solid Swing Door



Specifications subject to change without notice.

Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

0800 783 2049
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

true
REFRIGERATION