



MCX150M

Multideck with shutter

Product Features

- Ideal for impulse buys and promotions
- Lockable security shutter
- Ventilated cooling
- Adjustable shelves
- Fully automatic
- Castors with brake
- LED interior light with switch
- Digital controller and temperature display
- Ticket strip included

Stainless steel multidecks with lockable security shutter

The TEFCOLD MCX Range is an open front stainless steel multideck, ideal for grab and go and impulse purchases. It can be set to temperature suitable for drink, dairy or fresh meat to suit your requirements. The MCX also benefits from a rigid lockable security shutter to prevent access to product when food is not being served, it is also supplied on lockable castors to allow movement of the cabinet. This allows the unit to be more versatile as to where it can be utilised to maximise sales. The MCX Range is the perfect solution for a wide range of establishments such as cafeterias, hotels, schools, colleges, and university canteens. It caters to the need for a refrigerated multideck during service while also prioritising product security during non-service periods. This feature becomes especially valuable in environments where customers, staff, or students may still have access to the unit.

Measures and Content

Total Display Area	m ²	1.72
Temperature Range	°C	-1 to +5
Climate Class		3
Gross / Net Weight	kg	325 / 255
Gross / Net Volume	l	790 / 670

Design and Material

Shelves Number & Type		4 adjustable
Shelf Color		Stainless steel
Castors		Castors
Exterior Finish		SS304
Interior Finish		SS304
Interior Light		LED as option

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	2 x 150
Thermometer		Yes

Power and Consumption

Energy Class		F
Energy Consumption	kWh/24h	18.55
Annual Energy Consumption	kWh/year	6770
Power		13 Amp
Max Ambient		25°C 60% RH
Input Power	W	1210
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	61

Dimensions

Internal Dimension (WxDxH)	mm	1450 x 436 x 1250
External Dimension (WxDxH)	mm	1512 x 740 x 1994
Packed Dimension (WxDxH)	mm	1600 x 790 x 2150
40ft Container Load	pcs	14



Security shutter with lock



Strong castors