

C 80



D

Output

40 to 60 kg/h

A

SALES FEATURES

Automatic Sieves C 80 is designed to sieve preparations (sauce base, bisque, fish soup), to separate fibres from vegetables and to extract pulp from fruits.

B

TECHNICAL FEATURES

AUTOMATIC SIEVES C80 Single phase. Power 650W. 1 speed. Table top model. 100% stainless-steel construction. 1 perforated basket Ø 1 mm included (other baskets available in option). Continuous feed hopper. Continuous end-product and waste ejection chute. Model with an output from 40 to 60 kg/h.

Select all the options at the back page, **F** part.

C

TECHNICAL DATA

Output power	650 Watts	
Electrical datas	Single phase - Plug included	
Speeds	1500 rpm	
Dimensions (WxDxH)	620 x 360 x 520 mm	
Rate of recyclability	95%	
Net weight	21 kg	
Supply	Amperage	Reference
230V/50/1	5.7 Amp	55013

STANDARDS

EN 12100-1 & 2 - 2004, EN 60204-1 - 2006, EN 12852, EN 60529-2000



E

PRODUCT FEATURES/BENEFITS

MOTOR BASE

- **Induction direct drive motor** for intensive use.
- Power 650 Watts.
- 100% stainless-steel construction.
- Magnetic safety and motor brake.
- **1 speed : 1500 rpm.**

SIEVE FUNCTION

- **Continuous feed hopper** of washed products, no need to stone or peel for ease of use and time saving.
- **Continuous end-product ejection chute** : fruit and vegetable puree, coulis, soup...
- **Continuous waste ejection chute** : skins, pips, stones, tails, bones, shells, fibres.
- Paddle assembly rotating at 1500 or 1800 rpm to extract maximum pulp.
- All parts in contact with food are removable for a quick and easy cleaning.

INCLUDED ACCESSORIES


- 1 Perforated basket Ø 1 mm : for finely sieving

C 80

F

OPTIONS

- 1 Perforated basket Ø 0.5 mm - Ref. 57009
- 1 Perforated basket Ø 3 mm - Ref. 57008
- Additional rubber scraper (per unit) - Ref. 100338



G

DRAWINGS & DIMENSIONS

