

Ice-A-Cool ICE8950 Single Door Upright Refrigerator 580 Litres



The Ice-A-Cool ICE8950 Single Door Upright Refrigerator is constructed with a stainless steel exterior & interior and is equipped with a self-closing and stay open door.

- **⊘** Bottom mounted compressor unit
- Stainless steel interior and exterior construction
- ✓ Magnetic door gaskets
- ✓ Castors as standard
- Climate Class 4

- Self-closing and stay open door
- **⊘** Rounded interior corner design

| S P E C I F I C A T I O N S | | | | |
|-----------------------------|---------------------|-------------------------------|----------|--|
| Summary | | Power and Performance | | |
| Brand | Ice-A-Cool | Voltage (V/HZ/PH) | 220/50/1 | |
| Model | ICE8950 | Power (Watts) | 320 | |
| Shelf Quantity | 4 | Electrical Current (Amps) | 1.2 | |
| Material External | 201 Stainless Steel | Power Consumption (kWh/annum) | 913 | |
| Material Internal | 201 Stainless Steel | | | |

| Key Specifications | | Weights and Dimensions | |
|--------------------------------|-----------------------|--------------------------------|------------------|
| Gross Capacity (Litre) | 580 | Exterior Dimension (WxDxH) mm | 685 x 800 x 2112 |
| Nett Capacity (Litre) | 381 | Interior Dimension (WxDxH) mm | 565 x 640 x 1525 |
| Defrost Method | Air Defrost | Packing Dimension (WxDxH) mm | 740 x 860 x 2260 |
| Climate Class | 4 | Shelf Dimensions mm | 620 x 530 |
| Energy Efficiency Class | D | Insulation Thickness (mm) | 60 |
| Refrigerant | R600a | Shelf Loading Capacity (kg pc) | 40 |
| Cooling Method | Fan Assisted | Net Weight (kg) | 110 |
| Inner Temperature (°C) | +2°C to +8°C | Gross Weight (kg) | 120 |
| Foaming Material | C5H10 | Refrigerant Amount (g) | 120 |
| Castors | 4 (2 braked on front) | | |

