



LGF5000

Glass Door Display Freezer

Product Features

- Fully automatic, fan assisted cooling
- Automatic defrost
- Lock
- Adjustable shelves
- Castors and locking feet
- Self closing doors with stay open feature for ease of loading
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- Light canopy with switch
- Heated glass door to prevent condensation
- Internal stainless steel base

The TEFCOLD LGF5000 now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. The LGF500 comes equipped with an array of impressive features. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also a LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

Measures and Content

Total Display Area	m ²	1.38
Temperature Range	°C	-25 to -14
Climate Class		4
Gross / Net Weight	kg	210 / 190
Gross / Net Volume	l	1108 / 922

Design and Material

Door Number & Type	2 hinged glass doors	
Shelves Number & Type	8	
Exterior Finish	White	
Interior Finish	White	
Interior Light	2 x Vertically LED in door frame	

Cooling and Functions

Type of Cooling	Ventilated	
Type of Defrost	Automatic, electrical	
Refrigerant	R290	
Refrigerant Charge	g	150
Thermometer	Yes	

Power and Consumption

Energy Class	C	
Energy Consumption	kWh/24h	12.77
Annual Energy Consumption	kWh/year	4660
Power	13 Amp	
Max Ambient	30°C at 55% RH	
Input Power	W	1200
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	61

Dimensions

Internal Dimension (WxDxH)	mm	1262 x 640 x 1520
External Dimension (WxDxH)	mm	1382 x 800 x 2055
Packed Dimension (WxDxH)	mm	1430 x 860 x 2180
40ft Container Load	pcs	22



Internal fan



Strong castors