

Speed Queen®

TOPLOAD WASHERS AND DRYERS



- Commercial build quality = long life
- Extra large stainless steel wash tub
- Water saving wash cycles
- Simple electronic controls
- Gas or electric heat dryer options
- Reversible dryer door opens left or right
- Multiple dryer venting options
- Front serviceability on washer and dryer

LWN/LDE/LDG

SPECIFICATIONS	LWN Topload Washer
Control	Electronic
Capacity	7.5 kg
Drum Volume	92.3 litres
Width - in (mm)	25 5/8 (650)
Depth - in (mm)	28 (711)
Height - in (mm)	43 (1092)
Spin Speed	710 RPM
Motor Size - HP (kw)	1/2 (0.37)
Water Consumption per Cycle (litres)	92-130 depending on cycle selected
Available Water Temperatures	3
Available Cycles	Heavy Duty, Normal Eco, Perm Press, Delicate, Rinse and Spin, Spin Only
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)
Cycle Indicator Lights	Yes
Cylinder Finish	Stainless Steel
Electrical Requirements	240/50/1 - 13 Amp
Net Weight	82 kg
Shipping Weight - lb (kg)	88 kg
Shipping Width - in (mm)	27 1/2 (699)
Shipping Depth - in (mm)	30 (762)
Shipping Height - in (mm)	44 1/4 (1124)
Approvals	CE

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

SPECIFICATIONS	LDE/LDG Dryer
Control	Electronic
Models	Electric: LDE Gas: LDG
Capacity	8.2 kg
Cylinder Volume	200 litres
Width - in (mm)	26 7/8 (683)
Depth - in (mm)	28 (711)
Height - in (mm)	43 (1092)
Motor Size - HP (kw)	1/3 (0.25)
Available Heat Sources	Electric or Gas
Available Heating Element (Electric Model)	4800W*
Gas Inlet Connection - in (mm)	3/8 (9.5)
Gas Consumption - BTU/Hr	22,500
Exhaust Outlet Diameter - in (mm)	4 (102)
Exhaust Airflow - cfm (litres/sec)	220 (105)
Available Cycles	Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up
Cycle Indicator Lights	Yes
Cylinder Finish	Galvanized
Available Colours	White
Door Type (Solid/Window)	Solid
Electrical Requirements	Electric: 240/50/1 - 30 Amp* Gas: 240/50/1 - 13 Amp
Net Weight	Elec/Gas 59/61 kg
Shipping Weight - lb (kg)	Elec/Gas 64/67 kg
Shipping Width - in (mm)	29 (737)
Shipping Depth - in (mm)	32 3/4 (832)
Shipping Height - in (mm)	45 1/2 (1156)
Approvals	CE

* Other electric heat options are available - ask your supplier for details

DISTRIBUTED BY: