Lincat frifri



ECG9 - Silverlink 600 Electric Counter-top Chargrill - W 900 mm -13.3 kW

- Offers the authentic taste and branded appearance of chargrilled food without the need for lava rock
- High heat retention of cast iron grids means there is no waiting for the grill to recover to cooking temperature
- The water bath keeps food succulent and reduces shrinkage, while the high heat retention cast iron grids ensure your output stays high throughout operation

Create that distinctive chargrilled flavour and branded appearance without the need for messy lava rocks with the Silverlink 600 Electric Chargrill.

SILVERLINK 600

- Hinging interlocked elements and integral water bath makes cleaning easier
- Integral splashguard with water funnel enables refilling of tank without cooling the cooking grid
- High temperature safety cut out for protection if water bath runs dry

Specifications

	Power and Performance	
Silverlink 600	Total Power kW	13.3
Electric	IP Rating	IP33
Counter-top	Cooking Area (Width x Depth) mm	780 × 400
No	Temperature Control	Mechanical
2 Years Parts and Labour Warranty		
Contact your local dealer		
5056105104704		
	Weights and Dimensions	
5	Unit Height (External) mm	385
	Unit Width (External) mm	900
	Unit Depth (External) mm	620
	Net Weight Kg	49.4
	Shipping	
Yes	Packed Weight Kg	67
Yes	Packed Height cm	59.5
No	Packed Width cm	101.5
Yes	Packed Depth cm	72
13,300		
	Electric Counter-top No 2 Years Parts and Labour Warranty Contact your local dealer 5056105104704 5 5 5	Silverlink 800 Electric Counter-top IP Rating No Cooking Area (Width x Depth) mm 2 Years Parts and Labour Warranty Temperature Control Contact your local dealer S058105104704 5 Weights and Dimensions 5 Unit Height (External) mm Unit Width (External) mm Unit Width (External) mm Unit Weight Kg Shipping Yes Packed Weight Kg Yes Packed Width cm No Packed Width cm Yes Packed Depth cm

Available Accessories HCL9 Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 900 mm - 1.0 kW SLS9 Silverlink 600 Free-standing Floor Stand - for units W 900 mm


Technical Picture


Three Phase Voltage

400

Lincat frifri

SILVERLINK 600






Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk



Lincat frifri

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Export Customers

Tel: +44 1522 503250 Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm