

# Self Contained Icemakers

Introducing the self-contained icemaker range from DC. Crystalline ice on demand.



## Classic Ice




Solid cubes of crystalline ice that cools quickly and melts slowly - suitable for bars, night clubs, pubs, restaurants, healthcare industries, educational facilities, hotels and supermarkets.



Model	Production Kg's p/24hrs	Storage Kg	Dimensions mm (inc feet) W x D x H	Drain Height mm (inc feet)	Amps Required	Warranty Yrs
DC20-4A	20	4	355 x 405 x 610	145	13	3
DC25-6A	25	6	390 x 520 x 640	145	13	3
DC30-10A	30	10	390 x 520 x 720	145	13	3
DC35-16A	35	16	496 x 630 x 785	240	13	3
DC45-25A	45	25	496 x 630 x 895	240	13	3
DC55-25A	55	25	496 x 630 x 985	330	13	3
DC70-40A	70	40	737 x 640 x 1025	345	13	3
DC100-60A	100	60	737 x 640 x 1115	345	13	3
DC130-65A	130	65	840 x 740 x 1175	345	13	3
DC155-65A	155	65	840 x 740 x 1175	345	13	3



## Hollow Ice




Hollow cubes of crystalline ice that cools rapidly - particularly suited to hardwater areas due to the ice manufacturing process - suitable for bars, night clubs, pubs, restaurants, healthcare industries, educational facilities, hotels and supermarkets.



Model	Production Kg's p/24hrs	Storage Kg	Dimensions mm (inc feet) W x D x H	Drain Height mm (inc feet)	Amps Required	Warranty Yrs
DCi25-7	25	7	400 x 493 x 620	75	13	2
DCi25-10	25	10	450 x 515 x 685	75	13	2
DCi45-16	45	16	450 x 515 x 1000	185	13	2
DCi55-27	55	27	570 x 600 x 1000	185	13	2
DCi90-42	90	42	800 x 600 x 1000	185	13	2
DCi140-45	140	45	895 x 510 x 1200	258	13	2

## Granular Ice



Similar to crushed ice it's softer than cubes and chewable, while its mouldable qualities suit displays or packaging applications - suitable for cocktail bars, cafeterias, healthcare industries, carehomes, fast-food outlets, educational facilities, hotels, fishmongers, supermarkets, transport and processing operations.



Model	Production Kg's p/24hrs	Storage Kg	Dimensions mm (inc feet) W x D x H	Drain Height mm (inc feet)	Amps Required	Warranty Yrs
DCG90-20A	90	20	496 x 660 x 785	240	13	3
DCG90-30A	90	30	496 x 660 x 895	240	13	3
DCG150-40A	150	40	741 x 678 x 1025	345	13	3
DCG150-55A	150	55	741 x 678 x 1115	345	13	3

**Ambient air operating temperatures:**  
Minimum = +10°C Maximum = +38°C  
**Water inlet connection:** 3/4"

**Waste connection:** 21mm  
**Icemaker ventilation:** 200mm to the rear,  
50mm to the sides and top

Productions figures are based on a 20°C ambient operating temperature and 15°C water inlet temperature



**DC Products Ltd.**

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk [www.dcpowers.co.uk](http://www.dcpowers.co.uk)

