

Product specification



HR240: 240 Ltr Undercounter Cabinet Refrigerator

13-244

Reduced width undercounter refrigerator cabinet

Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Integrated door lock for added security
- High quality magnetic door gasket

mass (a)

- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- GN1/1 undercounter storage on a small footprint
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 40°C (ISO Climate Class 5)

Refrigerant	R290	Finish ext/int	304 S/S & Alu
Temperature	Refrigerator +1/+4°C	Number of sections Section configuration	2
Electrical supply	230/50/1		LeftHinge,RightHinge
Fuse rating (A)	10		
Current (A)	2.8	System	Integral
Power (W)	860		
Refrigerant	110		

Height (mm)	895	Climate Class	5
Width (mm)	870	Energy grade	Α
Depth (mm)	745	EEI	15.72
Gross volume	240	AEC (kWh)	339.35
(ltr)		Energy	0.93
Net volume (ltr)	144.2	consumption (kWh/24hr)	0.50
Leg type	Roller castors rear, levelling	(KWII/24III)	
	bolts front	GWP	1430
GN size	1/1		
Gross weight	100		
(kg)			
Net weight (kg)	86.5		

Footnotes

• For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.