



#### PRODUCT FEATURES

- Digital timer with 4 programmable settings for consistent cooking
- Audible alarm for perfect pasta every time
- Stainless steel construction for durability and easy cleaning
- Removable 8L tank with front drain tap for quick cleanup
- Corrosion-resistant elements and boil-dry protection for longevity
- Adjustable thermostat (25-100°C) for precise temperature control
- Four stainless steel baskets for cooking individual portions
- Non-slip feet for stability during use
- Ideal for cafes, restaurants, and high-volume kitchens

The Lynx Prime Countertop Pasta Cooker is perfect for efficient pasta cooking in busy kitchens. Built for heavy-duty use, it features a digital timer with four programmable settings and an audible alarm for consistent results, whether cooking spaghetti, ravioli, tagliatelle, or penne. The stainless steel construction includes a front drain tap and removable 8L tank for easy cleaning. With corrosion-resistant elements, boil-dry protection, and precise thermostat control, it ensures durability and perfect pasta every time. Ideal for cafes, restaurants, or catering, this cooker helps streamline your kitchen.

AIA FILE NUMBER:

ITEM NUMBER:



# LINCAT LYNX PRIME ELECTRIC COUNTER TOP PASTA COOKER - SINGLE TANK - 4 BASKETS W 280 MM 2.9 KW

## MODEL: LPPB

### WEIGHTS & DIMENSIONS

Width	385 mm
Depth	595 mm
Height	505 mm
Weight	10 kg

### SHIPPING DETAILS

Ship Width	385 mm
Ship Depth	595 mm
Ship Height	505 mm
Ship Weight	11.5 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ
Quick Ship Product	No
Ship Lead Time	1

### WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Type	Electric
Electrical Total Amperage	12.6 A
Electrical Volts	220-240V
Electrical Total Wattage	2900 W
Electrical Kilowatts	2.9 kW
Electrical Hertz	50 Hz

Electrical Phase	1-Phase
Electrical Plug Type	UK 3-Pin Plug
Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	No

### ADDITIONAL SPECIFICATIONS

Capacity (Volume)	8 l
Construction Materials	Stainless Steel
Control Type	Rotary Control Knob
Mixing Valve	No
Number of Baskets	4
Number of Vats (batteries)	1

Overflow Prevention	No
Ventless Cooking Technology	No
Temperature Maximum	100 °C
Temperature Minimum	25 °C
Water Fill	Manual

### BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.