



PANTHER

PRODUCT OPTIONS AND ACCESSORIES

- CP16 CP16 - CARVERY PAD [1/1 GASTRONORM SIZE]
- PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD
- PGK1 PGK1 - GASTRONORM PACK
- PGK2 PGK2 - GASTRONORM PACK
- PGK3 PGK3 - GASTRONORM PACK
- PHTC PHTC - CERAMIC INSERT [1/1 GASTRONORM SIZE]
- PHTG PHTG - GLASS INSERT [1/1 GASTRONORM SIZE]
- PPB6 PPB6 - ADDITIONAL PUSHBAR

PRODUCT FEATURES

- Ideal to fit through narrow corridors and doorways
- Bain marie top, ideal for small restaurants, cafes and pubs, as well as nursing and care homes, where the easy transportation of plated meals to diners and residents is a necessity
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 2 x 1/1 GN containers up to 150mm deep.
- Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- Drain tap located inside the hot cupboard allows fast and easy draining

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT PANTHER 670 SERIES FREE-STANDING HOT CUPBOARD - BAIN MARIE TOP - 2GN - W 980 MM - 2.6 KW

MODEL: P6B2

WEIGHTS & DIMENSIONS

| | |
|--------|---------|
| Width | 980 mil |
| Depth | 672 mil |
| Height | 912 mil |
| Weight | 80.9 kg |

SHIPPING DETAILS

| | |
|--------------------------|-------------------------|
| Ship Width | 100 cm |
| Ship Depth | 80 cm |
| Ship Height | 105 cm |
| Ship Weight | 88.99 kg |
| Ship Method | LTL Common Carrier |
| Shipping Package Type | Pieces |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|---------------------------|----------|--------------------------------------|---------------|
| Primary Energy Type | Electric | Electrical Plug Type | UK 3-Pin Plug |
| Electrical Total Amperage | 11.3 A | Number of Electrical Plugs | 1 |
| Electrical Volts | 230V | Electrical Connection Type | Cord and Plug |
| Electrical Total Wattage | 2600 W | Number of Electrical Conductor Wires | 1 |
| Electrical Kilowatts | 2.6 kW | Dedicated Circuit Required | No |
| Electrical Phase | 1-Phase | Electrical Remarks | Single |

ADDITIONAL SPECIFICATIONS

| | | | |
|------------------------|-------------------------------|---------------------------|--------|
| Plate Diameter Maximum | 12.75 in | Number of Doors | 2 |
| Plate Diameter Minimum | 11.25 in | Number of Shelf Positions | 4 |
| Cart Style | Plated Meals and Pans | Number of Shelves | 2 |
| Construction Materials | Stainless Steel | Plate Capacity | 222 |
| Control Type | Digital Touch Pad, Electronic | Shelf Depth | 512 mm |
| Gastronorm Capacity | 2 x GN1/1 | Shelf Width | 785 mm |
| Heating System | Electric | Temperature Maximum | 99 °C |
| | | Temperature Minimum | 20 °C |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
March 25, 2025

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

