

British Manufacturing since 1957



## The Professionals Choice

## CTS13SL

SureFlow Slim Line Counter Top Boiler



## **FULL SPECIFICATION**



## **SureFlow Slim Line Counter Top Automatic Fill Water Boiler**

Туре	Countertop - Slimline Range
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	OIX
Capacity (Litres)	13
Unit dimensions (W x D x H) mm	180 x 520 x 738 (depth includes drip-tray)
Packed dimensions (W x D x H) mm	298 x 578 x 825
Tap clearance mm	245mm
Product weight - empty (kg)	13.4
Product weight – full (kg)	28.8
Packed weight (kg)	16.1
CONSTRUCTION:	10.1
	204 grade Ctainless Ctael (Cunerbrush neligh)
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
ELECTRICAL:	•
Power rating (kW)	3
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (13A)
Plug type	UK standard 3-pin
Fitted cable length (m)	1.7m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Front via drip-tray (or rear using kit not supplied)
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	34 mins (full tank capacity)
Output per hour (every hour @ default temperature setting)	27 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	13 Litres
Recovery per minute	0.5 Litres
Stand-by power loss (idle mode)	0.09 kW/h
FILTRATION:	0.00 K()///
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	No (available as an optional extra il requirea)
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	165
Early warning lime-scale diagnostics (via LCD screen)	Yes – Basic
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	No (mode to M/DAC enceification 'i'm and minimal
WRAS approved	No (made to WRAS specifications awaiting submission)
EMC Compliant (EN 55014 & EN 61000)	Yes (self-certified)
Manufactured to meet BS Electrical Safety Standard	Yes (self-certified) – BS EN60335-1 & 2
WARRANTY & AFTER-SALES:	0.1
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

Instanta Limited T: 01704 501114 F: 01704 501115 E: sales@instanta.com





Certificate Numbers: FM01234 & EM01234