



**SILVERLINK 600**

#### PRODUCT OPTIONS AND ACCESSORIES

- SB7 750 GRIDDLE SPLASHB
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm

#### PRODUCT FEATURES

- Flexibility of a half smooth, half ribbed plate to give attractive branding lines to your food whilst being able to cook eggs on the smooth half of the plate. 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- Front mounted control for easy of use during cooking
- Piezo ignition for easy lighting of the burners
- Flame failure device for maximum safety

AIA FILE NUMBER:

ITEM NUMBER:



# LINCAT SILVERLINK NATURAL GAS COUNTER-TOP GRIDDLE - HALF-RIBBED PLATE - W 750 MM - 7.5 KW

## MODEL: GS7R/N

### WEIGHTS & DIMENSIONS

Width	750 mil
Depth	650 mil
Height	415 mil
Weight	54 kg

### SHIPPING DETAILS

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	59.4 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	7.5 kW	Gas Inlet Pressure Required	16 mBar
Electrical Connection Type	Not Applicable	Gas Total BTUs	25590 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	0.71 m <sup>3</sup>
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	7.5 kW, 23900 BTU per hour
Gas Type	Natural Gas	Energy Saving	No

### ADDITIONAL SPECIFICATIONS

Control Type	Mechanical	Lower Platen Surface Type (multi-select)	Smooth and Grooved
Cooking Area Plate Depth	405 mm	Number of Burners	2
Cooking Area Plate Width	712 mm	Number Of Controls	2
Cooking Plate Finish Material Type	Polished Steel	Number of Heating Zones	2
Food Production Rate	180 x 115g [4oz] burgers [frozen] per hour	Plate Shape	Rectangle
Legs or Casters	Not Applicable	Plate Thickness	12 mm
		Thermostat Element Location	Under Plate Mount

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
January 23, 2024

#### BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

#### TECHNICAL DRAWING

