

MODEL: P8P6PT



PANTHER

Helping to cater in demanding environments such as cafeterias, canteens and restaurants, the Panther 800 Series Hot Cupboard is perfect for plating and as a pass to front of house staff, while it also provides extra workspace or can be used as a mobile workstation. The unit is fan assisted, providing even heat distribution, fast heat up and recovery times, and lower energy usage. This model has sliding doors to both sides, providing enhanced workflow capability. Fully 1/1 GN compatible, this unit accomodates 6 x 1/1 GN containers up to 150mm deep, while the thermostatically controlled bain marie top can be operated with wet or dry heat. An accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations.

PRODUCT OPTIONS AND ACCESSORIES

PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD

PRODUCT FEATURES

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Pass through model with removable sliding doors to both sides provide enhanced workflow efficiency
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 6 x 1/1 GN containers up to 150mm deep.
- Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads







LINCAT PANTHER 800 SERIES FREE-STANDING HOT CUPBOARD -**PLAIN TOP - W 2180 MM - 2.5 KW**

MODEL: P8P6PT

WEIGHTS & DIMENSIONS	
Width	2180 mil
Depth	850 mil
Height	900 mil
Weight	197 kg

SHIPPING DETAILS	
Ship Width	222 cm
Ship Depth	90 cm
Ship Height	110 cm
Ship Weight	216.7 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS			
Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	10.9 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	2500 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	2.5 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS			
Plate Diameter Maximum	12.75 in	Number of Shelf Positions	4
Plate Diameter Minimum	11.25 in	Number of Shelves	2
Cart Style	Plated Meals and Pans	Plate Capacity	556
Construction Materials	Stainless Steel	Shelf Depth	512 mm
Control Type Dig	Digital Touch Pad, Elec-	Shelf Width	1929 mm
	tronic	Temperature Maximum	99 °C
Heating System	Electric	Temperature Minimum	20 °C
Number of Doors	4	-	

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 25, 2025






LINCAT PANTHER 800 SERIES FREE-STANDING HOT CUPBOARD - PLAIN TOP - W 2180 MM - 2.5 KW

MODEL: P8P6PT


BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 25, 2025

