



The Refrigeration Experts

Product specification



EP700F: 600 Ltr Cabinet Fish Refrigerator

41-232

- ✓ Designed specifically for delicate fish
- ✓ Advanced cooling system prevents ingredients from drying out
- ✓ In-built safety and hygiene features
- ✓ 7 hygienic storage boxes included

About the product

Explore the entire award-winning, energy saving [G3 fridge and freezer](#) range.

Why choose this product

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- The EP700F optimises fish storage conditions with the cooling system designed to prevent surface drying of the fish
- Operates in ambient temperatures of up to 43°C

Specification

Technical		Dimensions	
Temperature	Fish -1/+1°C	Height (mm)	2080
Thermal heat rejection (W)	190	Width (mm)	700
Electrical supply	230/50/1	Depth (mm)	825
Current (A)	0.95	Gross volume (ltr)	600
Power (W)	210	GN size	2/1
Refrigerant mass (g)	80	Gross weight (kg)	124
Refrigerant	R290	Net weight (kg)	118
Fuse rating (A)	10		

Build		Energy	
Cabinet type	Fish	Climate Class	4
Finish ext/int	304 S/S & 304 S/S	GWP	3
Number of sections	1		
Section configuration	Right hinge		
System	Integral		
Leg type	Braked castors		

Footnotes

- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm
- This product requires a drain.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.