

## Datasheets

### VarioSmoker Connector type G



#### Article number

60.75.373

#### Description

Give meat, fish and vegetables aromatic smoky flavours and unmistakable colours, you can define these yourself according to your preferences. The VarioSmoker allows you to cook and smoke food at the same time. This saves time, space and purchasing costs. A special smoker is no longer required.



#### Intended use

This product is only intended for commercial use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose, and could be dangerous. Any other use runs counter to its intended purpose, and could be dangerous.

This VarioSmoker was designed for smoking foods in RATIONAL combi steamers.

#### Features

- Can be used in manual mode in all RATIONAL combi-steamers manufactured from 1997
- Automatic control of the VarioSmoker by intelligent cooking paths in the iCombi Pro via the USB interface. These become active with the USB connection. The intelligence of the iCombi Pro provides for an optimal and professional cooking and smoking result in no time.
- Use of all conventional smoking materials

#### Technical Specifications

Connection:	100-240 V
Frequency:	50 Hz/60 Hz
Connected load:	165 W
Maximum Power consumption:	0,7-1,7 A

#### Dimensions and weights

	Weight (g)	Width (mm)	Height (mm)	Length (mm)
VarioSmoker (Smoking box):	1.530	121,2	69	437
Power supply unit:	1.250	110	91	270
Bracket long/short:	1.300/900	250	170	585/215
VarioSmoker cable:				3.000
USB cable:				2.000
Power supply cable:				1.800

#### Material

Smoking box:	Stainless Steel (CNS 1.4301)
Power supply unit:	Plastic PA6 Durethan
Bracket:	Stainless Steel (CNS 1.4301)

## Datasheets

### VarioSmoker Connector type G

---



#### Equipment/Scope of delivery

- USB connection cable
- Power supply unit
- Power supply bracket
- Application manual

#### Note

- The VarioSmoker must not be operated outside of the cooking system and only under an operational exhaust system. The smoke gases must be discharged from the building by the exhaust air system.
- Due to the shock hazard, the power supply unit may no longer be operated if the housing is damaged.
- An additional standard USB extension cable is required for use in the XS 6-2/3.
- The article is not suitable for use in the microwave

#### Approvals

