



# Product Code: MBCFT75

Modular Blast Chiller with 700mm door width c/w 25mm floor and integral ramp

---



## Features & Benefits

---

- MBCT models are supplied floorless for blast chilling application only
- Chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Intuitive easy touch control panel - Just press and go with easy to use colour coding to indicate cycle status.
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Operator-friendly fans cut-out whenever door is opened
- HACCP software is available as an option in 3 formats for data retrieval and management

## External Finish

White lam ext and door / white control panel	Standard
White lam ext, 304 s/s door and white control panel	Option
304 s/s ext	Option

## Doors

Solid	Standard
Left Hand Hinged Door	Option

## Product Extras

Hold Facility	Option
---------------	--------

## Internal Finish

White lam	Standard
304 s/s	Option

## Refrigeration

R404a - Industry Standard	Standard
Less Condensing Unit	Standard
Remote Refrigeration System	Standard

## Specification

Dimensions (Width)	1350
Dimensions (Height)	2350
Dimensions (Depth)	1330
Weight (Unpacked, kg)	790
Weight (Packed, kg)	790
Chilling Capacity (Kgs)	75
Gross Volume	75
RS485 connection for HACCP data logging	Option
Noise DbA @ 1M	TBC

## Shelving

Additional S/S Trayslides	Standard
Trolley - Gastronorm - 1/1 (Not Supplied)	Option
Trolley - Gastronorm - 2/1 (Not Supplied)	Option
Trolley Capacity - 690x1040x1890	Standard

## Electrical, Service & Ecodesign Data

230/50/1	Standard
----------	----------

## Footnotes

- MBC models are supplied floorless for blast chilling application only.
- Control panel sprayed white
- Capacity 75kg. Chilling capacity 70oC to 3oC in less than 90 minutes within specifications. Entry temperature or up to 90oC for chilling.
- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15oC e.g. Prep rooms
- Condensing Unit: All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral).



Energy



Quality



Value



Design



Hygiene



After Care