



Do your employees often have to wait in line for the office kettle to boil? Well, this FilterFlow Automatic Wall Mounted Water Boiler provides hot water on tap 24/7, making tea round lethargy a thing of the past. Compact for limited spaces, the boiler comes with a built-in water filtration system which improves the water quality. And changing the high-volume cartridges is as easy as changing a lightbulb.

#### PRODUCT OPTIONS AND ACCESSORIES

- DP10 DESCALER POWDER
- DR72 Drip Tray for FilterFlow WMB3F & WMB5F
- FC02 FILTER CARTRIDGE - 1 MICRON

#### PRODUCT FEATURES

- Exceptionally compact wall mounted design, perfect for locations with limited space
- High quality boiling water on tap 24 hours a day
- Built-in water filtration system improves water quality and reduces scale build-up
- Dispense temperature can be reduced to 70°C, perfect for delicate speciality teas
- High volume, easy change FilterFlow cartridge
- Allows extra room underneath the tap for larger cups, teapots, jugs and airpots to be filled
- Advanced diagnostics with LCD panel showing boiler status
- Cool-to-touch 6mm thick toughened glass fascia to withstand hard knocks

A/A FILE NUMBER:

ITEM NUMBER:



# LINCAT FILTERFLOW WMB WALL MOUNTED AUTOMATIC FILL BOILER - WHITE GLASS - 5L CAPACITY - 3.0 KW

## MODEL: WMB5F/W

### WEIGHTS & DIMENSIONS

Width	340 mil
Depth	184 mil
Height	462 mil
Weight	9.5 kg

### SHIPPING DETAILS

Ship Width	0 cm
Ship Depth	0 cm
Ship Height	0 cm
Ship Weight	10.45 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	13	Electrical Connection Type	Direct Hardwired
Electrical Voltage	230 volts	Electrical Plug Type	Hardwired
Electrical Watts	3000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	3 kW	Energy Saving	No

### ADDITIONAL SPECIFICATIONS

Capacity Volume	5.5 l	Internal Filter	Yes
Control Type	Electronic	Rapid Draw Off Hot	5.5 l
Dispense Actuation Method	Lever	Rapid Draw Off Hot Cups	28 C
Drip Pan	No	Temperature Maximum	96 °C
Hourly Hot Water Output	28 l	Temperature Minimum	70 °C
Hourly Number of Hot Cups	140		

### BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

