

Technical specification

Maxiglass MG3/315GCS bottle cooler

MG3/315GCS

Maxiglass plug ready glass door bottle cooler



Features and benefits

- The MG3 has been engineered with a fully foamed shell, driving significantly improved temperature performance
- Dimmable LED lights create a beautifully illuminated display area, encouraging impulse purchases
- The MG3 is one of the greenest bottle coolers on the market, with up to 30% energy savings compared to the previous range and R600a environmentally friendly refrigerant as standard
- Innovative flat shelving design ensures no more 'wobbly' bottles, allowing effortless stocking and retrieval of drinks
- Low maintenance condenser design reduces the risk of blockages, meaning that the refrigeration system doesn't have to work so hard
- Top mounted door locks are supplied as standard, keeping contents safe and secure

Refrigerant	R600A
Temperature	Refrigerator +6°C
Electrical supply	220-240V/50/60/1
Current (A)	1.2
Power (W)	190
Refrigerant mass (g)	58

Door material	S/S frame, glass
Finish ext/int	
Hinge	Hinged
Number of sections	3
Section configuration	Left hinge-Right hinge-Right hinge
System	Integral

Height (mm)	900
Width (mm)	1350
Depth (mm)	575
Capacity	366 x 330ml bottles 415 x 250ml bottles
Gross volume (ltr)	371
Gross weight (kg)	112
Net weight (kg)	103

Climate Class	CC2
Energy grade	D
EEl	49
AEC (kWh)	781
Energy consumption (kWh/24hr)	2.14
GWP	3
Min - max temperature (°C)	+2/+18

Footnotes

- Height is adjustable from 900 to 910mm
- Allow an extra 10mm to the side of the cabinet for optimal airflow
- Depth of the cabinet is excluding handgrip, including power supply connection

Thank you for your interest in this product. We hope you now have everything you need to choose Gamko, however if you have any further questions, please do not hesitate to contact us.

Gamko, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.gamko.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.