

R3-1500



D

Number of meals per service

10-30 covers

Amount processed per

0.3-1.5 kg

A

SALES FEATURES

The **R3-1500 table-top cutter** is ideal for grinding, mincing and kneading, as well as for making mousses, emulsions and smooth stuffings. It effortlessly performs even the lengthiest task in just a few minutes, consistently producing a flawless end product.

B

TECHNICAL FEATURES

R3-1500 table-top cutter. 230V/50Hz/1ph. Power: 650 W. Speed: 1,500 rpm. 3.7-l stainless-steel bowl with handle, plus bowl-base, smooth-edged, twin-blade assembly. 10-30 covers.

Select the options you want from the list in Section **F** overleaf.

C

TECHNICAL CHARACTERISTICS

Output power	650 W
Electrical data	230V/50Hz/1ph 5.7 A – plug supplied
Speed	1,500 rpm
Dimensions (WxDxH)	210 x 320 x 400 mm
Rate of recyclability	95%
Net weight	13 kg
Reference	22383

CE MARKING

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006,
EN 12852, EN 60529-2000 - IP55 - IP34

E

PRODUCT FEATURES / BENEFITS

MOTOR UNIT

- **Industrial direct-drive (no belt) induction motor** designed for intensive use
- Power 650 W
- Stainless-steel motor shaft
- Motor base made from heavy-duty composite material
- Magnetic safety system, thermal failsafe and motor brake
- **Single speed 1,500 rpm**
- **Pulse function** for greater cutting precision

CUTTER FUNCTION

- **3.7-l stainless-steel cutter bowl** with handle for better grip
- **Bowl-base blade assembly** with two high-strength, stainless-steel, smooth-edged blades for homogeneous processing even for small amounts
- **Central lid opening** for adding liquid or solid ingredients during processing
- High heat- and shock-resistant **see-through lid** to monitor processing from start to finish
- All parts are dishwasher-safe and can easily be removed for cleaning

STANDARD ATTACHMENTS

- 3.7-l bowl with lid
- Blade assembly with two smooth-edged, stainless-steel blades and a detachable cap

R3-1500

F OPTIONAL ATTACHMENTS

- Coarse-serrated, twin-blade assembly for grinding and kneading – Ref. 27288
- Fine-serrated, twin-blade assembly for chopping herbs and grinding spices – Ref. 27287
- Additional smooth-edged, twin-blade assembly – Ref. 27286

**Coarse-serrated****Fine-serrated****G**

DRAWINGS AND DIMENSIONS

230 V / 50 Hz / 1 ph – power cord and plug supplied

