



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- GR3/BS BENCH STAND FOR GR3 - H410,D350,W605
- ABP03 BRANDING PLATE KIT
- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- GR3/FS FLOOR STAND FOR GR3 - H1260,D350,W605
- GR3/WS WALL SHELF FOR GR3

PRODUCT FEATURES

- Powerful ceramic plaque burners for rapid heat up
- 5 shelf positions to give maximum flexibility for all catering operations
- Chrome wire shelf to allow trays and food to be placed on for cooking
- Cool touch handles for safety
- Enamelled interior and hood for easy cleaning

Sometimes during fast turnaround times, you need to be able to toast and grill at speed. The Silverlink 600 Gas Salamander Grill is ideal for these scenarios. Perfect for any modestly-sized, fast-paced restaurant, pub or takeaway, the grill boasts powerful ceramic plaque burners for rapid heat up, with five shelf positions to give maximum flexibility for all catering operations. Easy to clean, it also comes with a chrome wire shelf to allow trays and food to be placed on for cooking. Producing perfectly grilled meat, fish, and toast has never been as simple or stress-free.

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK PROPANE GAS COUNTER-TOP SALAMANDER GRILL - W 600 MM - 5.0 KW

MODEL: GR3/P

WEIGHTS & DIMENSIONS

| | |
|--------|---------|
| Width | 600 mil |
| Depth | 423 mil |
| Height | 408 mil |
| Weight | 20.5 kg |

SHIPPING DETAILS

| | |
|--------------------------|--------------------------------|
| Ship Width | 70 cm |
| Ship Depth | 55 cm |
| Ship Height | 49.5 cm |
| Ship Weight | 22.55 kg |
| Ship Method | Small Parcel (FedEx, UPS, DHL) |
| Shipping Package Type | Pieces |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | |
|-------------------------------------|--------------------------|
| Primary Energy Type | Gas |
| Electrical Kilowatts | 5 kW |
| Gas Type | Propane |
| Gas Total BTUs | 17060 BTU |
| Gas Inlet Size | 0.5 in |
| Gas Inlet Pressure Required | 37 mBar |
| Gas Consumption at Max Use Per Hour | 0.36 m ³ |
| Total Heat Input at Max Use | 5 kW, 17100 BTU per hour |

ADDITIONAL SPECIFICATIONS

| | | | |
|----------------------------|-----------------|-----------------------------|---|
| Broiler Base Configuration | Not Applicable | Food Production Rate | 42 x 115g [4oz] burgers [frozen] per hour |
| Broiler Type | Salamander | Heat Location | Top Only |
| Construction Materials | Stainless Steel | Heat Source Type | Ceramic |
| Control Type | Mechanical | Number of Heating Zones | 1 |
| Cooking Area Plate Depth | 225 mm | Number of Shelf Positions | 4 |
| Cooking Area Plate Width | 410 mm | Ventless Cooking Technology | No |

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

