





### **COMPACT AND VERSATILE**

With our solid engineering and design background, Hoshizaki develops cabinets for better storage solutions for Chefs and kitchen operators.



### **UNIFORM TEMPERATURES**

Automatic defrost and a smart air distribution system ensures correct and uniform temperatures at all times preserving the taste, texture and nutritional content of your fresh goods.



### SPACE SAVING MODULARITY

The COMPACT undercounter models are designed to fit under worktops in commercial workplaces. They can be positioned as free-standing cabinet. The full-height storage cabinets boast a small footprint, perfect for limited space in back of house environment.



### **EASY CLEANING**

Rounded corners and base, seamless surfaces and removable door gasket ensures cleaning routines become a quick and simple task.



### **WASTE REDUCTION**

The practical anti-tilting shelves prevent spillage.



### **FULL HEIGHT INTEGRATED HANDLE**

Easy grip and easy access for cleaning.



### HIGH STANDARD IN HYGIENE

The one piece inner lining with its smooth surfaces and seamless construction allows for a straight forward cleaning routine.

## A quick guide to the Compact series.







- The GRAM COMPACT series offers a rare combination: they are professional food safe cabinets with a compact size and with excellent energy ratings for its class.
- These small space storage cabinets are easy to fit in, especially when space is of a premium, making the COMPACT series a popular choice amongst small kitchen operators who do not require heavy duty gastronorm refrigeration.
- Ideal for commercial kitchens.
  (Front of House/ Back of House)
- Suitable for operations in ambient temperatures of up to +30°C.
- Climate Class 4: normal-duty cabinets (KG-glass door refrigerators-are also climate class 4) Climate Class 3: glass door freezers.

1>

Low noise levels.

2)

Air circulation system ensure temperature stability.

3>

Removable door gasket for easy cleaning.

4>

Full-height integrated handle. Easy grip and easy access for cleaning.

5>

Anti-spillage shelves with tilt prevention.

6>

Automatic defrost.

7>

Compact 220 fits under work tops or can be stacked if required.

8>

Variety of cabinet size and temperature ranges.

9>

Seamless structure for easy cleaning inside the cabinet.

10>

Optional: pedal door opener, which can be placed on left or right side.



<11

Built-in LED light (available in glassdoor cabinets only).

<12

Wide magnetic removable door gasket with triple insulation area provides an effective seal, reduces escaping cold air.

₹13

Efficient air distribution inside the cabinet allows chilled air flow with a specially designed air channel.

< 14

Reversible door (solid or glass doors).

< 15

According to your preference: Legs or Castors available (420 models only).

< 16

Clear display. Membrane switchboard for easy cleaning.

< 17

Automatic re-evaporation of condensate water.

<18

Door Lock.









# A range of Compact cabinets for versatile kitchen set-ups

### **ABOUT COMPACT**

The COMPACT series offers a rare combination: they are professional food safe cabinets with a compact size and with excellent energy ratings for its class. The COMPACT series benefits from a small footprint and versatility. Compact food storage has never been better.









### THE COMPACT FAMILY







220









164220010 +1/+12°C

230V/50 Hz
100
A
429
4
38.8
R600a
3
2
483.8 x 433
484.7 x 300

Item number
Temperature range
Volume, gross (I)
Net usable volume (I)
Outside dimensions W x D x H (mm
Weight (kg)
Weight, packed (kg)
Insulation (mm)
Refrigeration capacity at -10°C (W)
Refrigeration capacity at -25°C (W)
Connection
Connection load (Watt)
Energy efficiency class
Energy consumption AEC (Annual)
Climate class
Sound level db(A)
Refrigerant
GWP (Global Warming Potential
Number of shelves
Shelf size of top shelves (mm)
Shelf size of bottom shelves (mm)
Maximum number of shelves

151220010	161220010	154220010
+1/+12°C	+1/+12°C	+1/+12°C
123	123	123
77	77	77
595 x 645 x 833	595 x 645 x 833	595 x 667 x 833
43	43	49
52	52	58
52 (polyurethane)	52 (polyurethane)	52 (polyurethane)
63	63	82
-	-	-
230V/50 Hz	230V/50 Hz	230V/50 Hz
70	70	100
A++	A++	А
197	197	429
4	4	4
38.8	38.8	38.8
R600a	R600a	R600a
3	3	3
2	2	2
483.8 x 433	483.8 x 433	483.8 x 433
484.7 x 300	484.7 x 300	484.7 x 300
9	9	9

iviaximum number of sneives	9 9	
ITEM	ADD ON	
1519898	Wire shelf white 485*433	
1519899	Wire shelf white bottom 485*300	
1129664	Set of stainless steel (SS) adjustable foot 135-200mm	
1129665	Set of castor for Compact	
761230421	White perforated shelf (486x433mm)	
819581052	Foot pedal for door	

AVAILABLE FOR
All models
All models
K420, F420, KG420, FG420
K420, F420, KG420, FG420
All models
All models

### Notes for accessories

COMPACT K420R L1 DR G E

**L1** indicates that these models are fitted with legs (1129663)

Please find accesories list recommendation for models with legs.

## 220









	COMPACT F220R DR G E	COMPACT F220L DR G E	COMPACT FG220R DR G E	COMPACT FG220L DR G E
Item number	153220010	163220010	155220010	165220010
Temperature range	-25/-5°C	-25/-5°C	-19/-5°C	-19/-5°C
Volume, gross (I)	123	123	123	123
Net usable volume (I)	77	77	77	77
Outside dimensions W x D x H (mm)	595 x 645 x 833	595 x 645 x 833	595 x 667 x 833	595 x 667 x 833
Weight (kg)	44	44	52	52
Weight, packed (kg)	53	53	61	61
Insulation (mm)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)	52 (polyurethane)
Refrigeration capacity at -10°C (W)	-	-	-	-
Refrigeration capacity at -25°C (W)	186	186	186	186
Connection	230V/50 Hz	230V/50 Hz	230V/50 Hz	230V/50 Hz
Connection load (Watt)	150	150	150	150
Energy efficiency class	A	A	С	С
Energy consumption AEC (Annual)	700	700	906	906
Climate class	4	4	3	3
Sound level db(A)	39.2	39.2	39.2	39.2
Refrigerant	R600a	R600a	R600a	R600a
GWP (Global Warming Potential)	3	3	3	3
Number of shelves	2	2	2	2
Shelf size of top shelves (mm)	483.8 x 433	483.8 x 433	483.8 x 433	483.8 x 433
Shelf size of bottom shelves (mm)	484.7 x 300	484.7 x 300	484.7 x 300	484.7 x 300
Maximum number of shelves	9	9	9	9

ITEM
1519898
1519899
1129664
1129665
761230421
819581052

ADD ON
Wire shelf white 485*433
Wire shelf white bottom 485*300
Set of stainless steel (SS) adjustable foot 135-200mm
Set of castor for Compact
White perforated shelf (486x433mm)
Foot pedal for door

AVAILABLE FOR	
All models	
All models	
K420, F420, KG420, FG420	
K420, F420, KG420, FG420	
All models	
All models	

### Notes for accessories

COMPACT K420R L1 DR G E

**L1** indicates that these models are fitted with legs (1129663)

Please find accesories list recommendation for models with legs.

420



COMPACT K420R L1 DR G E







Item number	
Temperature range	
Volume, gross (I)	
Net usable volume (I)	
Outside dimensions W x D x H (n	nm)
Weight (kg)	
Weight, packed (kg)	
Insulation (mm)	
Refrigeration capacity at -10°C (	W)
Refrigeration capacity at -25°C (	W)
Connection	
Connection load (Watt)	
Energy efficiency class	
Energy consumption AEC (Annu-	al)
Climate class	
Sound level db(A)	
Refrigerant	
GWP (Global Warming Potent	ial)
Number of shelves	
Shelf size of top shelves (mm)	
Shelf size of bottom shelves (m	m)
Maximum number of shelves	

151421010
+1/+12°C
343
265
595 x 645 x 1876-1911
76
87
52 (polyurethane)
122
-
230V/50 Hz
120
В
310
4
39.8
R600a
3
5
483.8 x 433
484.7 x 300
26

161421010	154421010
+1/+12°C	+1/+12°C
343	343
265	265
595 x 645 x 1876-1911	595 x 667 x 1876-1911
76	89
87	99
52 (polyurethane)	52 (polyurethane)
122	122
-	-
230V/50 Hz	230V/50 Hz
120	130
В	D
310	670
4	4
39.8	39.8
R600a	R600a
3	3
5	5
483.8 x 433	483.8 x 433
484.7 x 300	484.7 x 300
26	26

GE	COMPACT KG420LL1 DR G E
	164421010
	+1/+12°C
	343
	265
	595 x 667 x 1876-1911
	89
	99
	52 (polyurethane)
	122
	-
	230V/50 Hz
	130
	D
	670
	4
	39.8
	R600a
	3
	5
	483.8 x 433
	484.7 x 300
	26

ITEM
1519898
1519899
1129664
1129665
761230421
819581052

ADD ON
Wire shelf white 485*433
Wire shelf white bottom 485*300
Set of stainless steel (SS) adjustable foot 135-200mm
Set of castor for Compact
White perforated shelf (486x433mm)
Foot pedal for door

AVAILABLE FOR
All models
All models
K420, F420, KG420, FG420
K420, F420, KG420, FG420
All models
All models

### Notes for accessories

COMPACT K420R L1 DR G E

L1 indicates that these models are fitted with legs (1129663)

Please find accesories list recommendation for models with legs.

### 420



COMPACT F420R L1 DR G E




163421010

-25/-5°C

343

265 595 x 645 x 1876-1911





COMPACT FG420LL1 DR G E

165421010

-19/-5°C

Item number	
Temperature range	
Volume, gross (I)	
Net usable volume (I)	
Outside dimensions $W \times D \times H$ (r	nm)
Weight (kg)	
Weight, packed (kg)	
Insulation (mm)	
Refrigeration capacity at -10°C	(W)
Refrigeration capacity at -25°C	(W)
Connection	
Connection load (Watt)	
Energy efficiency class	
Energy consumption AEC (Annu	al)
Climate class	
Sound level db(A)	
Refrigerant	
GWP (Global Warming Potent	tial)
Number of shelves	
Shelf size of top shelves (mm)	
Shelf size of bottom shelves (m	m)
Maximum number of shelves	

153421010
-25/-5°C
343
265
595 x 645 x 1876-1911
77
88
52 (polyurethane)
-
217
230V/50 Hz
140
С
1086
4
39.7
R600a
3
5
483.8 x 433
484.7 x 300
26

77
88
52 (polyurethane)
-
217
230V/50 Hz
140
С
1086
4
39.7
R600a
3
5
483.8 x 433
484.7 x 300
26

155421010
-19/-5°C
343
265
595 x 667 x 1876-1911
97
110
52 (polyurethane)
-
217
230V/50 Hz
140
В
1152
3
39.7
R600a
3
5
483.8 x 433
484.7 x 300
26
483.8 x 433 484.7 x 300

343
265
595 x 667 x 1876-1911
97
110
52 (polyurethane)
-
217
230V/50 Hz
140
В
1152
3
39.7
xR600a
3
5
483.8 x 433
484.7 x 300
26

ITEM
1519898
1519899
1129664
1129665
761230421
819581052

ADD ON
Wire shelf white 485*433
Wire shelf white bottom 485*300
Set of stainless steel (SS) adjustable foot 135-200mm
Set of castor for Compact
White perforated shelf (486x433mm)
Foot pedal for door

AVAILABLE FOR		
All models		
All models		
K420, F420, KG420, FG420		
K420, F420, KG420, FG420		
All models		
All models		

### Notes for accessories

COMPACT K420R L1 DR G E

**L1** indicates that these models are fitted with legs (1129663)

Please find accesories list recommendation for models with legs.

