

British Manufacturing since 1957



The Professionals Choice

CTSP17H

SureFlow Plus Counter Top with built in Filtration (High Level Tap)





SureFlow Plus Counter Top Automatic Fill Water Boiler with built in Filtration (High Level Tap)

| Туре | Countertop - Premium Range |
|---|---|
| Country of Design & Manufacture | UK |
| | |
| CAPACITY, WEIGHTS & DIMENSIONS: | 17 |
| Capacity (Litres) | |
| Unit dimensions (W x D x H) mm | 360 x 555 x 705 (depth includes drip-tray) 470 x 600 x 820 |
| Packed dimensions (W x D x H) mm | |
| Tap clearance mm | 304mm (extra clearance for tall jugs, teapots & cafetieres) |
| Product weight - empty (kg) | 20.2 39.5 |
| Product weight – full (kg) | |
| Packed weight (kg) | 22.8 |
| CONSTRUCTION: | |
| Outer fabrication (body) construction | 304 grade Stainless Steel (Superbrush polish) |
| Tank construction | 304 & 316 grade Stainless Steel |
| Tank wall thickness | 0.9mm |
| Drip-tray | 304 grade Stainless Steel – (Mirror polish) |
| ELECTRICAL: | |
| Power rating (kW) | 3 |
| Voltage supply | 230 V (50-60Hz) |
| Electrical supply | Single-phase, N & E (13A) |
| Plug type | UK standard 3-pin |
| Fitted cable length (m) | 1.7m |
| PLUMBING: | |
| Water inlet connection: | 3/4" BSP |
| Food quality, flexible mains water hose | 1.6 metre long, (3/4"BSP) |
| Mains water pressure range | 2 – 7 bar (28psi – 100psi) |
| Overflow/waste connection: | Choice of front (via drip-tray) or rear (1/2"BSP – 15mm) |
| PERFORMANCE: | |
| Water temperature delivered | 96°C (default) – can be adjusted if required |
| Heat up time to working temperature | 48 mins (full tank capacity) |
| Output per hour (@ default temperature setting) | 28 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off | 17 Litres |
| Recovery per minute | 0.5 Litres |
| Stand-by power loss (idle mode) | 0.09 kW/h |
| FILTRATION: | |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | Yes |
| Filter Benefits | Latest triple-action; removes sediment & impurities such as |
| | chlorine and reduces limescale build-up |
| Max recommended filter capacity | 13,500 (or 6 months) |
| Mechanical sediment filtration | 3 micron |
| Filter counter programmable | Yes (between 2000 & 19,500 litres) |
| OTHER FEATURES: | |
| 7 day programmable timer | Yes |
| Energy saving ECO mode | Yes |
| Tank-baffle plates – unique design aids heat recovery & | Yes |
| reduces steam emissions to atmosphere | |
| Early warning lime-scale diagnostics (via LCD) | Yes |
| Dual safety protection | Yes - Over-boil & boil-dry protection |
| STANDARDS & APPROVALS: | |
| WRAS approved | Yes |
| EMC Tested and Certified (EN 55014 & EN 61000) | Yes |
| Electrical Safety Tested and Certified to BS standard | Yes (BS EN 60335-1 & 2) |
| WARRANTY & AFTER-SALES: | |
| Guarantee | 2 Year parts & labour |
| Spare parts, filters & accessories | Same day despatch (if ordered before 3pm) |
| טימוט אמונס, ווונפוס ע מטטפססטוובס | oano day despaton (ii ordered belore spin) |

Instanta Limited

T: 01704 501114 F: 01704 501115 E: <u>sales@instanta.com</u>

