

UNDERCOUNTER DISHWASHER 800

Bar Aid
German engineered for market-leading quality
by **HOBART**



With renowned German engineering, the Bar Aid range from Hobart delivers market-leading quality at really competitive prices. Offering exceptional wash results, unquestionable reliability and low running costs, Bar Aid is the ideal and convenient solution to your dishwashing needs, available exclusively through the dealer network.

You need...

- ✓ User friendly...
- ✓ Good hygiene standards...
- ✓ Easy to access...
- ✓ Outstanding results...
- ✓ Optimum water quality...
- ✓ Fast performance...
- ✓ Streak free...
- ✓ Cost efficient...
- ✓ Easy to clean...
- ✓ Choice of wash cycles...

Bar Aid delivers...

single button control – easy to use and understand
hygienic self flushing cycle on shut down with two stage strainer to remove debris
chamber and wash tank with polished interior – no dirt traps
powerful pump delivers total wash coverage via separate upper and lower wash and rinse arms
optional built-in water softener ensures the finest water quality to deliver a sparkling finish
capable of up to 40 cycles per hour (approx. 160 covers)
integral detergent and rinse aid pumps deliver precise dosing
saves on water, energy and detergent
only six removable items for cleaning
standard 90 second cycle plus longer 180 second cycle for heavy soiling

Tel: 0870 168 8881

www.hobartindependent.co.uk

UNDERCOUNTER DISHWASHER 800

SPECIFICATIONS

General	800
Dimensions	600mm(w) 600mm(d) 820mm(h)
Depth Door Open	1046mm
Number of racks	1 x plate rack, 1 x open rack, 1 x cutlery basket
Rack size	500 x 500mm
Max pints/plates per rack	18
Max racks p/h	40
New Weight (kg)	60
Rinse booster pump	YES
Built in detergent dispenser	YES
Built in rinse aid dispenser	YES
Double skinned door	YES
Controls	ELECTRONIC
Class A air gap	YES
Thermostop Control	YES
Programme times. secs	90 – 180
Water consumption/cycle	2.5L
Wash tank capacity	10.6L
Wash tank heating	0.8kW
Rinse tank capacity	6.8L
Drain pump	YES
Wash pump rating	0.6kW
Wash pump flow rate	200L/min
Rinse pump rating	0.1kW
Rinse pump flow rate	115L/min
Noise level (dB)	62
Water	
Water pressure	0.8 – 6 BAR
Water temp	MAX 60°C
Electric	
Voltage 3P	400/50/3
Voltage 1P	230/50/1
Total loading 3P	3 x 16A/7.6kW
Total loading 1P	25A/5.6kW(default)



Technical details may be subject to change at any time without prior notice.

HOBART INDEPENDENT

Southgate Way, Orton Southgate,
Peterborough PE2 6GN

0870 168 8881

or visit www.hobartindependent.co.uk

