

WARE WASHING

MMERCIAL DISHWA

P/N 1302066





# SALES DESCRIPTION

Commercial dishwasher with 3 wash cycles and thermal cycle delay option included.

## FEATURES AND BENEFITS

- ✓ For washing glasses, cups, cutlery and small plates.
- $\checkmark$  3 wash cycles with final cold rinse.

 $\checkmark$  Manufactured from catering grade AISI 304 2B stainless steel and incorporating top quality components.

 $\checkmark$  Double skinned door with high efficiency seal, ensuring thermal and acoustic insulation. Magnetic door micro-switch.

✓ Removable stainless steel rack holders ensure even distribution of wash water without dead zones. Precision positioned water jets guarantee optimum washing result for even the most stubbornly stained glasses. Easy to assemble, boltless rinse spray arms.

 $\checkmark$  A double filter system provides effective wash pump protection that is easily removed (for maintenance and cleaning) and replaced, without tools.

 $\checkmark$  Inside of the machine with rounded finished: absence of angles avoiding the accumulation of dirt.

 $\checkmark$  Completely rounded, stainless steel wire rack support and guide.

- ✓ Automatic detergent and rinse aid dosing equipment.
- ✓ Electronic control panel with anti-moisture seal.

 $\checkmark$  Adjustable washing tank and boiler temperature and security in the boiler.

 $\checkmark$  Rinse boiler temperature adjustment and a thermal cycle delay option, guaranteeing a minimum final rinse temperature of 85°C for each and every rinse cycle.

✓ Sammic ware washers are designed for easy and fast on-site maintenance.

100% tested.

### NCLUDES

equipment.

- ✓ Rinse aid doser.
- ✓ Variable detergent dosing

✓ Drain pump and non-return

- valve.
- 1 open basket.
- 1 mixed basket.
- ✓ 1 small cutlery basket.





www.sammic.co.uk Food Service Equipment Manufacturer Unit 2, Trevanth Road

Troon Industrial Park LE4 9LS - Leicester uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	



# DISHWASHER X-45B 230/50/1 DD (WITH DRAIN PUMP)

Compact dishwasher. 450x450mm. racks. Max. loading height: 280mm.

## **SPECIFICATIONS**

Basket dimensions: 450 mm x 450 mm Maximum glass height: 280 mm Cycle duration: 90 " / 120 " / 150 "

- Production baskets/hour: 40/30/24
- Wash temperature: 50 °C 65 °C
- Rinse temperature: 75 °C 85 °C
- ✓ Boiler capacity: 6.5 I
- ✓ Wash tank capacity: 23 I
- ✓ Water consumption/cycle: 2.9 I
- ✓ Electrical supply: 230 V / 50 Hz / 1 ~ (13.4 A)
- ✓ Plug: -

### Loading

 $\checkmark$ 

- ✓ Pump: 370 W / 0.5 Hp
- ✓ Tank: 1500 W
- ✓ Boiler: 2500 W
- ✓ Total loading: 2870 W


## External dimensions (WxDxH)

- √ Width:520 mm
- ✓ Depth: 590 mm
- ✓ Height: 795 mm

Net weight: 51.5 Kg

#### **Crated dimensions**

- 565 x 645 x 915 mm
- Gross weight: 57.6 Kg.



## Accessories

- □ Stands for glass- and dishwashers
- Dosing equipments
- Manual water softeners
- Automatic water softeners
- □ 450 x 450 mm. baskets
- Inserts, supplements & similar
- High Feet Kit



www.sammic.co.uk Food Service Equipment Manufacturer

Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester uksales@sammic.com

uksales@sammic.com Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

**NARE WASHING**