



Product Code: HR360

Refrigerated Undercounter Cabinet



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 40°C

External Finish		Internal Finish		Shelving	
s/s ext	Standard	aluminium	Standard	Nylon Coated Shelf	Option
Base Fittings		Doors		Refrigeration	
Levelling Bolts	Standard	Solid	Standard	R290 - Energy Efficient	Standard
Electrical, Service & Ecodesign Data		Specification		R134a - Industry Standard	Option
				Integral Refrigeration System	Standard
230/50/1	Standard	Dimensions (Width)	1217		
Fuse Required	13	Dimensions (Height)	824		
Global Warming Potential	3	Dimensions (Depth)	755		
Energy Efficiency Index	40.05	Weight (Unpacked, kg)	90.5		
Refrigerant Charge	0.150	Weight (Packed, kg)	104.51		
kWh (24 hours)	2.76	Gross Volume	360		
		Noise DbA @ 1M	TBC		

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care