





PASSTHROUGH DISHWASHERS

The Ecomax range of passthrough dishwashers (also known as hood types) is efficient and economical. Perfectly suited to any busy kitchen, the robust, high quality range is sure to meet your operational requirements.

ECOMAX H602/S VERSUS ECOMAX PLUS H603/S

RACKS PER HOUR LOADING HEIGHT 48 **ECOMAX ECOMAX** 440 MM ECOMAX PLUS **ECOMAX PLUS** 60 440 MM CYCLE TIME (secs) WATER CONSUMPTION per cycle **ECOMAX** 75-150 **ECOMAX** 2.8L **ECOMAX PLUS** 60-90 **ECOMAX PLUS** 2.5L

Turn over for full machine specs.





SPECIFICATIONS	ECOMAX	ECOMAX PLUS	
GENERAL	H602/S	H603/S	
DIMENSIONS	635mm(w) 740mm (d)	635mm (w) 740mm(d)	
Height hood open	1960mm(h)	1960mm (h)	1
Width with handle	715mm	715mm	
Number of racks	1 x plate rack, 1 x cutlery basket	1 x plate rack, 1 x open rack, 1 x cutlery basket	
Loading height	440mm	440mm	
Rack size	500 x 500mm	500 x 500mm	
Max pints/plates per rack	18	18	
Max racks p/h	48	60	
New weight (kg)	100	105	Tess (see)
Rinse booster pump	YES	YES	- "
Built in detergent dispenser	YES	YES	u j
Built in rinse aid dispenser	YES	YES	-
CONTROLS	ELECTRONIC	ELECTRONIC	ECOMAX H602/S
Class A air gap	YES	YES	
Thermostop control	YES	YES	
Programme times. secs	75 - 150	60 - 90	
Water consumption/cycle	2.8L	2.5L	
Wash tank capacity	21L	21L	
Wash tank heating	2.5kW	2.5kW	, //
Rinse tank capacity	5.6L	5.6L	
Drain pump	YES	YES	
Wash pump rating	0.4kW	0.7kW	
Wash pump flow rate	225L/min	400L/min	
Rinse pump rating	0.27kW	0.1kW	
WATER		1 1	THE RESERVE TO SERVE THE PARTY OF THE PARTY
Integral softener	YES	YES	
Water pressure	0.8 – 6 BAR	0.8 – 6 BAR	
Water temp	MAX 60°C	MAX 60°C	2
ELECTRIC		· ·	1
Voltage 3P	400/50/3	400/50/3	. i i ,
Voltage 1P	230/50/1	230/50/1	•
	1		
Total loading 3P	3 x 16A/6.6kW (Factory setting)	3 x 16A/7.0kW (Factory setting)	ECOMAX PLUS H603/S

Technical details may be subject to change at any time without prior notice.

Tabling not included.