



*Opus 800*

With a half ribbed plate option for attractive branding presentation marks, the Opus 800 Gas Ribbed Plate Griddle is designed to create appetizing food accurately. The griddle comes with an accurate thermostatic control up to 300°C for consistent results and an economical operation. Perfect for any busy commercial kitchen, it utilizes a maximised cooking area, with the griddle plates to the sides of the unit. Built for safety, the griddle also comes with convenient piezo ignition and pilot burners for stand-by operation, as well as flame failure protection.

#### PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- OA8917/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 600 mm
- OA8917 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 600 mm
- OA8972/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 600 mm
- OA8972 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 600 mm

#### PRODUCT FEATURES

- Half ribbed plate option for attractive branding presentation marks
- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Precise thermostatic control up to 300°C for consistent results and economical operation
- Convenient piezo ignition and pilot Burners for stand-by operation
- Flame failure protection

**WEIGHTS & DIMENSIONS**

Width	600 mm
Depth	800 mil
Height	532 mm
Weight	76.5 kg

**SHIPPING DETAILS**

Ship Width	70 cm
Ship Depth	800 cm
Ship Height	63 cm
Ship Weight	84.15 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	15.5 kW	Gas Inlet Pressure Required	37 mBar
Electrical Connection Type	Not Applicable	Gas Total BTUs	52886 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	1.11 m <sup>3</sup>
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	15.5 kW
Dedicated Circuit Required	Yes	Energy Saving	No
Gas Type	Propane		

**ADDITIONAL SPECIFICATIONS**

Control Type	Mechanical	Number of Burners	2
Cooking Area Plate Depth	600 mm	Number Of Controls	2
Cooking Area Plate Width	590 mm	Number of Heating Zones	2
Cooking Plate Finish Material Type	Half Grooved Steel Plate	Plate Shape	Rectangle
Food Production Rate	96 x 225g [8oz] steaks [chilled] per hour	Plate Thickness	15 mm
Legs or Casters	Not Applicable	Temperature Maximum	280 °C
Lower Platen Surface Type (multi-select)	Smooth and Grooved	Temperature Minimum	90 °C
		Thermostat Element Location	Under Plate Mount

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

