



## LGC5000 Black

Glass Door Merchiser

### Product Features

- Fully automatic
- Fan assisted cooling
- Automatic defrost
- Lock
- Adjustable shelves
- Castors and locking feet
- LED interior light with switch (2 LED strips per door)
- Digital controller and temperature display
- LED Light canopy with switch
- Internal stainless steel base
- Self closing doors with stay open feature for ease of loading

The TEFCOLD LGC5000 chiller now available in a sleek black finish. This exciting update allows the unit to seamlessly blend into various retail and catering environments, making it an excellent choice for establishments seeking a sophisticated and high-quality aesthetic. Each door boasts two vertical LED light strips, these draw attention to the product on display giving a striking contrast against the black interior of the cabinet. There is also an LED light canopy which is ideal for branding and advertising. The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. Additionally, the carefully engineered refrigeration system is highly energy-efficient, minimising operational costs while keeping your products at their optimal temperature. The unit is also fitted with castors, to allow moving for cleaning purposes and other necessary adjustments.

### Measures and Content

Total Display Area	m <sup>2</sup>	1.38
Temperature Range	°C	+1 to +8
Climate Class		4
Gross / Net Weight	kg	210 / 190
Gross / Net Volume	l	1108 /

### Design and Material

Door Number & Type	2 hinged glass doors	
Tempered glass		Yes
Shelves Number & Type		8
Max load on Shelves	kg/m <sup>2</sup>	196
Exterior Finish		Black
Interior Finish		Black
Interior Light	2 x Vertically LED in door frame	

### Cooling and Functions

Type of Defrost	Off Cycle	
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes

### Power and Consumption

Energy Class		B
Energy Consumption	kWh/24h	5.21
Annual Energy Consumption	kWh/year	1900
Power		13 Amp
Max Ambient		30°C at 55% RH
Input Power	W	400
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	58

### Dimensions

Internal Dimension (WxDxH)	mm	1262 x 640 x 1520
External Dimension (WxDxH)	mm	1382 x 800 x 2055
Packed Dimension (WxDxH)	mm	1430 x 860 x 2180
40ft Container Load	pcs	22



Illuminated canopy



Strong castors