

COOL PRODUCTS WORLDWIDE



Galaxy+ GP26 White

Multideck

Product Features

- Fully automatic, fan assisted cooling
- Horizontal LED lighting
- Solid 40 mm endwalls with mirrored interior
- Soft closing nightblind
- Adjustable shelves, max weight 160kg/sq metre
- \bullet Shelves can be flat or angled to 7° or 14°
- EPOS Ticket strips & shelf risers
- Suitable for fresh meat
- Can be multiplexed with kit (POA)

Open front multideck

The TEFCOLD Galaxy+ open front is our latest innovation in plugin multidecks. We've combined an expanded display area and optimised cabinet efficiency that easy access to customers for impulse buys with excellent LED lighting. The cabinets come with 39mm EPOS ticket strips together with shelf risers as standard. The 5 Shelves can be angled at 7 or 15 degrees to give more options for merchandising and creating an attractive display for your customers. The Galaxy+ open range is suitable for fresh meat, dairy and drinks. It is ideal for use in supermarkets, convenience stores, farm shops, delis and sandwich shops.

Measures and Content		
Total Display Area	m²	3.83
Temperature Range	°C	-1 to +5
Climate Class		3
Gross / Net Weight	kg	460 / 430
Gross / Net Volume	I	2887 / 1258
Design and Material		
Shelves Number & Type		5 adjustable
Shelf Color		White
Shelf Dimensions		1250x400mm
Max load on Shelves	kg/m²	160
Feet / Legs		6 adjustable feet
Exterior Finish		White RAL9003
Interior Finish		White RAL9003
Interior Light		LED
Lock		No
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	2 x 150
Thermometer		Yes
Power and Consumption		
Energy Class		E
Energy Consumption	kWh/24h	29.57
Annual Energy Consumption	kWh/year	10793
Power		16 Amp
Max Ambient		25°C at 60% RH
Input Power	W	868
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	55
Dimensions		
Internal Dimension (WxDxH)	mm	2500 x 544 x 1562
External Dimension (WxDxH)	mm	2580 x 740 x 2040
Packed Dimension (WxDxH)	mm	2650 x 770 x 2320
40ft Container Load	pcs	8