

## Induction Oven Range

900mm wide

PHER01 & PHER01/SPH

- Six 1.85Kw zones. When you need intense heat to get you cooking zones can be boosted to 3Kw
- Incredible efficiency, reducing running costs and providing a more comfortable kitchen environment
- Easy to clean heavy duty 6mm thick high impact resistant glass ceramic surface
- Large 6 x GN1/1 capacity twin fan assisted oven enabling six different foods to be cooked simultaneously
- Highly insulated oven reducing heat loss and ensuring a more consistent temperature



### Induction Hob Features

- 6mm thick high impact glass ceramic surface
- Multiple internal cooling fans
- Overheat protection
- Automatic pan detection switches cooking zone off when pan removed
- LED power indication
- No pan-present indication
- Error mode indication
- Long life induction system – 10,000 hours
- Easy to change air filters

### Cleaning and Servicing

#### Oven Features

- 6kW heating element
- Precision thermostatic control from 50 °C to 250 °C
- Twin fan assisted oven
- Power ON indicator light (green)
- 180° side hinged doors
- Oven capacity 6 x GN1/1
- Heavy-duty easy remove wire chrome rack supports
- 4 position racking with anti-tilt guards and safety stops

### Cleaning and Servicing

- 6mm thick ceramic glass cooking surface, easy clean, spillages can just be wiped away
- Easy clean stainless steel external finish
- Heavy-duty easy remove wire chrome rack supports
- Stainless steel oven lining with removable base liner
- Easy change generator air filter

### Overall Construction

- Permanent laser etched markings on fascia and knobs
- 1.2 mm stainless steel base panel
- 0.8 mm stainless steel side panels
- Castors as standard

### Induction Hob Construction

- 1.2 mm stainless steel welded bull nose and hob surround

### Oven Construction

- 0.8 mm stainless steel outer door skin
- Reinforced door seal
- Double insulated doors and side panels
- Stainless steel oven liner

### Inclusive Accessories

- 2 chrome plated shelves

### Available Options

- Adjustable legs

### Available Accessories

- FI36 Filter kit

## Technical Data

	PHER01	PHER01/SPH
Width (mm)	900	900
Depth (mm)	800	800
Hob height (mm)	900	900
Cooking area w x d (mm)	800 x 545	800 x 545
Usable oven capacity h x w x d (mm)	419 x 770 x 530	419 x 770 x 530
Oven shelf size w x d (mm)	770 x 530	770 x 530
Hob	6 zones	6 zones
Hob rating per induction zone (kW)	1.85, boost 3.0	1.85, boost 3.0
Hob rating per pair zones (kW)	3.7	3.0
Oven rating (kW)	6.0	4.0
Total electrical power rating (kW)	17.1	13.0
Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps)	L1 = 25 L2 = 25 L3 = 25	N/A
Electrical supply 1 Supply 1N~+E 230V 50-60Hz Current Rating (Amps)	N/A	56.5
Electrical supply 2 Supplies 1N~+E 230V 50-60Hz Current Rating (Amps)	N/A	30.4 26.1
Net weight (kg)	150	150
Packed weight (kg)	164	164
Shipping volume (m3 )	0.909	0.909
IPX Protection	IPX4	IPX4

