



**PANTHER**

**PRODUCT OPTIONS AND ACCESSORIES**

- CP16 CP16 - CARVERY PAD [1/1 GASTRONORM SIZE]
- PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD
- PGK1 PGK1 - GASTRONORM PACK
- PGK13 PGK13 - GASTRONORM PACK
- PGK15 PGK15 - GASTRONORM PACK
- PGK16 PGK16 - GASTRONORM PACK
- PGK18 PGK18 - GASTRONORM PACK
- PGK2 PGK2 - GASTRONORM PACK
- PGK3 PGK3 - GASTRONORM PACK
- PGK4 PGK4 - GASTRONORM PACK
- PGK7 PGK7 - GASTRONORM PACK
- PHTC PHTC - CERAMIC INSERT [1/1 GASTRONORM SIZE]
- PHTG PHTG - GLASS INSERT [1/1 GASTRONORM SIZE]
- PPB8 PPB8 - ADDITIONAL PUSHBAR

**PRODUCT FEATURES**

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 5 x 1/1 GN containers up to 150mm deep.
- Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- Drain tap located inside the hot cupboard allows fast and easy draining

AIA FILE NUMBER:

ITEM NUMBER:

**WEIGHTS & DIMENSIONS**

Width	1855 mil
Depth	850 mil
Height	912 mil
Weight	146 kg

**SHIPPING DETAILS**

Ship Width	188 cm
Ship Depth	90 cm
Ship Height	110 cm
Ship Weight	160.6 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	22.6	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	5200	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	5.2 kW	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Cart Style	Plated Meals and Pans	Number of Shelves	2
Control Type	Digital Touch Pad, Electronic	Plate Capacity	476
Gastronorm Capacity	5 x GN1/1	Plate Diameter	11.25" to 12.75"
Heating System	Electric	Shelf Depth	512 mm
Legs or Casters	Casters	Shelf Width	1610 mm
Number of Doors	2	Temperature Maximum	99 °C
Number of Shelf Positions	4	Temperature Minimum	20 °C

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

