

Vector® H Series Multi-Cook Oven

CE Certified

ALTO-SHAAM

Providing an unmatched volume and variety of food, compact and ventless Vector H Series countertop models are specifically designed for foodservice operations where space is at a premium, but food demand is high.

Featuring up to four independent oven chambers, operators can control the temperature, fan speed and cook time in each individual chamber for maximum flexibility – simultaneously cooking a variety of menu items with no flavor transfer.

Exclusive Structured Air Technology® delivers focused heat for faster, more even cooking and consistent, high-quality results.

Reduce labor by eliminating extra steps in food production and the need to watch and rotate pans.

Place anywhere with a small, 533mm footprint and ventless, waterless operation.

An advanced control – designed intentionally simple – features an intuitive, user-friendly interface and programmable recipes to ensure consistency with each cook.

Custom colors available for enhanced branding and a front-of-house experience for customers.

ChefLinc™, cloud-based remote oven management software, streamlines processes and maximizes profits with data-driven insights (Deluxe control only).

ISO 9001:2015-certified



VMC-H4H VMC-H3H VMC-H2H

Standard Features

- Programmable, touchscreen control
- Easy recipe upload/download via USB port
- Double-pane glass door
- One [1] wire stainless steel rack and two [2] jet plates per cooking chamber
- 102mm adjustable legs



- 2 VMC-H2H: 2 shelf, 2 GN 1/1—530mm x 325mm x 65mm or 2 GN 2/3 pans—354 mm x 325 mm x 65mm
- 3 VMC-H3H: 3 shelf, 3 GN 1/1—530mm x 325mm x 65mm or 3 GN 2/3 pans—354 mm x 325 mm x 65 mm
- 4 VMC-H4H: 4 shelf, 4 GN 1/1—530mm x 325mm x 65mm or 4 GN 2/3 pans—354 mm x 325 mm x 65mm

Configurations (select one)

Models

These models accommodate GN1/1 pans

- VMC-H2H
- VMC-H3H
- VMC-H4H

Control

- Deluxe
- Simple

Kit

- Ethernet Cable [5030518] for Deluxe only

Door swing

- Right hinged
- Left hinged

Electrical

VMC-H2H

- 220–240V, 1PH, no cord, no plug
- 380–415V, 3PH, no cord, no plug

VMC-H3H

- 220–240V, 1PH, no cord, no plug
- 380–415V, 3PH, no cord, no plug

VMC-H4H

- 380–415V, 3PH, no cord, no plug

Accessories (select all that apply)

- See accessories brochure for all available accessories

Casters and Legs

- 76mm casters, set of four (4) (5027946)

Cookware

- Jet plate assembly, hotel pan (5025236)
- Wire rack (SH-37662)
- Wire shelf, hotel pan (SH-39077)

Cleaning

- Alto-Shaam® non-caustic cleaner, one (1) bottle (CE-46828)
- Alto-Shaam® non-caustic cleaner, case of six (6) bottles (CE-46829)

Grease Filters

- Internal chamber filters—order one (1) kit per chamber (5027119)




IP X4



Vector® H Series Multi-Cook Oven

Specification



DIMENSIONS

Model	Exterior (H x W x D)
VMC-H2H	752mm x 546mm x 1003mm
VMC-H3H	929mm x 546mm x 1003mm
VMC-H4H	1108mm x 546mm x 1003mm

Model	Interior (H x W x D)
VMC-H2H	366mm x 373mm x 546mm
VMC-H3H	544mm x 373mm x 546mm
VMC-H4H	721mm x 373mm x 546mm

Model	Net Weight
VMC-H2H	97 kg
VMC-H3H	126 kg
VMC-H4H	158 kg

Model	Ship Dimensions (L x W x H)*
VMC-H2H	1219mm x 762mm x 1422mm
VMC-H3H	1219mm x 762mm x 1422mm
VMC-H4H	1219mm x 762mm x 1422mm

Model	Ship Weight*
VMC-H2H	150 kg
VMC-H3H	167 kg
VMC-H4H	198 kg

*Domestic ground shipping information. Contact factory for export weight and dimensions.



CLEARANCE

Top:	51mm*
Left:	51mm
Right:	51mm
Front:	508mm
Back:	51mm



CHECK FIRST

- The oven must be installed level.
- The oven must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.
- Oven not intended for built-in installation.

* 457mm recommended for service access

Vector® H Series Multi-Cook Oven



HEAT

Heat of rejection

VMC-H	Heat Gain qs, BTU/hr	Heat Gain qs, kW
	1,898	0.56



TEMPERATURE

Maximum temperature: 274°C



ELECTRIC


VMC-H2H	V	Ph	Hz	IEC	A	Breaker [A]	kW	Plug Configuration	Certification
220-240V	220	1	50/60	4	25	32	5.4	No cord, no plug	CE EAC IP X4
	240	1	50/60	4	28	32	6.4	No cord, no plug	
380-415V	380	3	50/60	1.5	8	16	5.4	No cord, no plug	CE EAC IP X4
	415	3	50/60	1.5	9	16	6.4	No cord, no plug	
VMC-H3H									
220-240V	220	1	50/60	10	37	63	8.1	No cord, no plug	CE EAC IP X4
	240	1	50/60	10	41	63	9.6	No cord, no plug	
380-415V	380	3	50/60	1.5	13	16	8.1	No cord, no plug	CE EAC IP X4
	415	3	50/60	1.5	14	16	9.6	No cord, no plug	
VMC-H4H									
380-415V	380	3	50/60	4	17	32	10.8	No cord, no plug	CE EAC IP X4
	415	3	50/60	4	18	32	12.7	No cord, no plug	

Vector® H Series Multi-Cook Oven




Stacked Configurations and Stands

VMC-HxH on stand 5034115




Dimensions shown are with adjustable feet at minimum height.

VMC-H on stand 5034118



Dimensions shown are with casters at minimum height.

VMC-H on stand 5034294



Dimensions shown are with adjustable feet at minimum height.




Scan or click the QR code for Vector stands guide

Vector® H Series Multi-Cook Oven




Stacked Configurations and Stands

VMC-HxH on stand 5033311 over VMC-H3H with casters




Dimensions shown are with adjustable feet at minimum height.




Other Bottom Unit Options

300-TH, 500-S, 500-TH, 500-IDN, 500-2DN, 500-3DN, VMC-H2H

VMC-HxH on stand 5033314 over VMC-H4H with casters



Dimensions shown are with adjustable feet minimum height.



Other Bottom Unit Options


300-TH; 500-S; 500-TH; 500-IDN; 500-2DN; 500-3DN; VMC-H2H; VMC-H3H



Scan or click the QR code for Vector stands guide

Alternative Stacked Configurations and Stands

VMC-HxH on stand 5033317 over VMC-H3H




Dimensions shown are with adjustable feet at minimum height.

Other Bottom Unit Options

300-TH, 500-S, 500-TH, 750-TH, 750-S, 500-ID, 500-2D, 500-3D, 500-2DI, 500-1DN, 500-2DN, 500-3DN, VMC-H2H, VMC-H2HW

VMC-HxH on stand 5033384 over VMC-H2H, or VMC-H2HW



Dimensions shown are with casters at minimum height.

Other Bottom Unit Options

300-TH, 500-S*, 500-TH, 750-TH, 750-S*, 500-ID, 500-2D, 500-3D, 500-2DI, 500-1DN, 500-2DN, 500-3DN

*Excluding ovens with 127mm casters




Scan or click the QR code for Vector stands guide

Vector® H Series Multi-Cook Oven



Alternative Stacked Configurations and Stands

VMC-HxH on stand 5033479 over 500-TH




Dimensions shown are with adjustable feet at minimum height.

Other Bottom Unit Options

300-TH, 500-S, 500-TH, 500-IDN, 500-2DN, 500-3DN

CTX4-10 on stand 5033312 over VMC-H3H



Dimensions shown are with adjustable feet at minimum height.

Other Bottom Unit Options

300-TH, 500-S, 500-TH, 500-IDN, 500-2DN, 500-3DN, VMC-H2H

CONTACT US

W164 N9221 Water Street | Menomonee Falls, Wisconsin 53051 | U.S.A.
 Phone: 262.251.3800 | 800.558.8744 U.S.A./Canada | Fax: 262.251.7067 | alto-shaam.com