



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SB6 600 GRIDDLE SPLASHB
- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

PRODUCT FEATURES

- Fully ribbed cooking area to give attractive branding lines to your food
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Hard wearing 12 mm thick machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

Whether you're cooking bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. It comes with two separately controlled heat zones which give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously. The griddle also features a fully ribbed cooking area to give attractive branding lines to your food. It's perfect for cafes, pubs and restaurants.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	620 mil
Height	330 mil
Weight	41 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	45.1 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Kilowatts	4 kW
Electrical Amps	Single Phase 17.4/Three Phase L1=8.7; L2=8.7; L3=N/A	Number of Electrical Conductor Wires	1
Electrical Voltage	230 volts/400 volts	Electrical Plug Type	Hardwired
Electrical Watts	4000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single, Three	Dedicated Circuit Required	Yes
		Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob	Number of Heating Zones	2
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	562 mm	Plate Thickness	12 mm
Cooking Plate Finish Material Type	Grooved Steel	Temperature Maximum	250 °C
Legs or Casters	Not Applicable	Temperature Minimum	50 °C
Lower Platen Surface Type (multi-select)	Grooved	Thermostat Element Location	Under Plate Mount
Number Of Controls	2		

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

