



Standard Extra Dishwashers

Introducing the new Standard Extra Range Dishwashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



Standard Extra Range

SXD40
SXD45
SXD50

- **Fast**
- **Economical**
- **Energy Efficient**
- **Space Saving**



Performance

My Wash cycle

four fixed and one self configurable cycles

New innovative wash pump

increases wash pressure improving results

Hydrodynamic basket slides

ensures optimum wash and rinse coverage

Rinse thermo-lock

delivers perfect rinse temperatures time after time

Upgraded boiler element

for improved recovery times

Energy and Cost Savings

Standby mode

configurable to suit your personal environment

Double skinned door and cabinet

reduces noise and heat emissions whilst lowering running costs

Reduced water consumption

produces the optimum balance between water usage and hygiene

Improved rinse arms

increases initial response by 30% and rotation speed by 20%

Insulated boiler

lowers running costs and improves boiler recovery times

Operation

Intuitive, simple, digital controls

complete with manager menu and temperature readouts

EasyClean filters

maintenance friendly filters protect critical components

Chemical auto-dosing

controlled via interface, improves results and prevents over or under dosing

Auto drain down (optional)

ensures rapid drain down with no need for user intervention

Integral water softener (optional)

softens water without the need for an external unit

'Welcome to a cleaner world'

Standard Extra Range Dishwasher Specifications

14



14



18



	SXD40	SXD45	SXD50
Cycle time	60 90 120 180 User Defined	90 120 180 300 User Defined	90 120 180 300 User Defined
Baskets (x3)	450 x 450 mm	450 x 450 mm	500 x 500 mm
Height	690 mm	795 mm	825 mm
Width	475 mm	535 mm	580 mm
Depth	540 mm	575 mm	635 mm
Depth with door open	885 mm	930 mm	1015 mm
Usable wash height	290 mm	290 mm	315 mm
Drain height	120 mm	180 mm	200 mm
Drain Ø	25 mm	25 mm	25 mm
Wash tank	18 lts	22 lts	26 lts
Boiler	2.8 lts	2.8 lts	2.8 lts
Water usage	2.4 lts p/c	2.6 lts p/c	2.6 lts p/c
Wash element	1.6 kW	2 kW	2 kW
Boiler element	2.8 kW	6 kW	6 kW
Total load	4.7 kW	6.4 kW	6.4 kW
Amps required	20 Amps**	30 Amps**	30 Amps**
Detergent dosing	Yes	Yes	Yes
Rinse aid dosing	Yes	Yes	Yes
Water connection	3/4 BSP	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar	2-4 bar
Required water flow rate	10 lts p/min	10 lts p/min	10 lts p/min
Drain pump	Optional	Optional	Optional
Internal softener*	Optional	Optional	Optional
Break tank (WRAS)	Optional	Optional	Optional

Where water hardness exceeds 100ppm a water softener is required.

* Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 125 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

** Can be configured to operate on either 13A or 3Ph+N upon request.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

