



Opus **800**

PRODUCT OPTIONS AND ACCESSORIES

- OA8991/C Lincat Opus 800 Free-standing Floor Stand with Castors - for Synergy Grill W 600 mm
- OA8991 Lincat Opus 800 Free-standing Floor Stand with Legs - for Synergy Grill W 600 mm

PRODUCT FEATURES

- Suites with Opus 800 series
- Patented award winning Synergy Grill technology delivers incredibly hot temperatures yet uses an average of 59% less gas than a standard grill
- Gently smokes food, giving you incredible flavour
- Clear contrasting bar marks
- Quickest grill on the market to clean, once cold, you can simply vacuum out the dust that's left
- No fat means no fat tray to clean
- The simplest grill on the market to operate
- Safety is paramount, one of the safest units to operate

Synergy Grills enable you to prepare food faster at less than half the energy costs. Fat atomising technology means there's no fat tray to clean and best of all, it creates seriously succulent food.

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT OPUS NATURAL GAS SYNERGY GRILL - W 600 MM - 5.7 KW

MODEL: OG8410/N

WEIGHTS & DIMENSIONS

| | |
|--------|---------|
| Width | 600 mm |
| Depth | 800 mil |
| Height | 790 mm |
| Weight | 95.4 kg |

SHIPPING DETAILS

| | |
|----------------------------|-------------------------|
| Ship Width | 70 cm |
| Ship Depth | 800 cm |
| Ship Height | 104 cm |
| Ship Weight | 104.94 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|--------------------------------------|---------------|-------------------------------------|----------------------------|
| Primary Energy Source Type | Gas | Dedicated Circuit Required | No |
| Electrical Amps | 10 | Gas Type | Natural Gas |
| Electrical Voltage | 230 volts | Gas Inlet Size | 0.5 in |
| Electrical Watts | 5700 | Gas Inlet Pressure Required | 20 mBar |
| Electrical Phase | Single | Gas Total BTUs | 19448 BTU |
| Kilowatts | 5.7 kW | Gas Consumption at Max Use Per Hour | 0.54 m ³ |
| Number of Electrical Conductor Wires | 1 | Total Heat Input at Max Use | 5.7 kW, 19448 BTU per hour |
| Electrical Connection Type | Cord and Plug | Energy Saving | Yes |
| Electrical Plug Type | UK 3-Pin Plug | | |
| Number of Electrical Plugs | 1 | | |

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 23, 2024



MODEL: OG8410/N

ADDITIONAL SPECIFICATIONS

| | | | |
|--------------------------|------------------------------------|-------------------------|-------------------|
| Base Type | Not Applicable | Ignition Type | Electric Ignition |
| Burner Material | Stainless Steel | Legs or Casters | Not Applicable |
| Charbroiler Type | Countertop | Number of Burners | 1 |
| Control Type | Mechanical, Rotary Control Knob | Number Of Controls | 1 |
| Cooking Area Plate Depth | 495 mm | Number of Heating Zones | 1 |
| Cooking Area Plate Width | 520 mm | Radiant Material | Stainless Steel |
| Grate Type | Cast Iron | Slide Out Warming Rack | No |
| | | Towel Bar | Yes |

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

