





GLASSWASHERS

Our research indicates that 94% of customers would be put off going to an outlet again if confronted with dirty glassware. Ecomax glasswashers make it quick, simple and cost effective to deliver a high quality finish, every time.

ECOMAX G502 VERSUS ECOMAX PLUS G503/S

RACKS PER HOUR MAX GLASS CLEARANCE HEIGHT 355 MM **ECOMAX ECOMAX ECOMAX PLUS ECOMAX PLUS** 425 MM CYCLE TIME (secs) WATER CONSUMPTION per cycle **ECOMAX** 60-180 **ECOMAX** 2.9L **ECOMAX PLUS** 90-120 ECOMAX PLUS 2.5L **DOUBLE SKINNED CONSTRUCTION** ECOMAX DOOR ONLY Turn over for full machine specs. **ECOMAX PLUS FULL MACHINE**





SPECIFICATIONS GENERAL	ECOMAX G502	ECOMAX PLUS G503/S
Max Glass Clearance Height	355mm	425mm
Depth Door Open	1046mm	1046mm
Number of racks Rack size Max pints/plates per rack Max racks p/h New weight (kg) Rinse booster pump Built in detergent dispenser Built in rinse aid dispenser Double skinned construction CONTROLS Class A air gap Thermostop control Programme times. secs Water consumption/cycle Wash tank capacity Wash tank heating Rinse tank capacity Drain pump Wash pump rating Wash pump flow rate	1 x 4 division glass rack 500 x 500mm 20 60 64 NO YES YES DOOR ELECTRONIC NO YES 60 – 180 2.9L 25L 2.0kW 5.6L YES 0.37kW 220L/min	1 x 5 division glass rac 500 x 530mm 25 40 60 YES YES YES FULL ELECTRONIC YES YES 90 – 120 2.5L 10.6L 0.8kW 6.8L YES 0.6kW 200L/min
Rinse pump rating WATER	0.25kW	0.1kW
Integral softener Water pressure Water temp ELECTRIC	NO 2 – 6 BAR N/A	YES 0.8 – 6 BAR MAX 60°C
Voltage 3P	400/50/3	400/50/3
Voltage 1P Total loading 3P	230/50/1 3 x 16A/6.0kW	230/50/1 3 x 16A/7.7kW

25A/4.2kW(Factory setting)

13A/2.3kW

25A/5.6kW(Factory setting)

13A/2.8kW



ECOMAX G502



ECOMAX PLUS G503/S

Technical details may be subject to change at any time without prior notice.

Total loading 1P