

# Datasheets

## Stand XS model XS 6 2/3



### Article number

60.31.029

### Description

The stand ensures a safe, elevated installation of the Combi-Duo, consisting of iCombi Pro XS, CombiMaster Plus XS and SelfCookingCenter XS. The cooking system can be fixed on the base frame using a mounting kit.



### Intended use

This product is only intended for commercial use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose, and could be dangerous. Any other use runs counter to its intended purpose, and could be dangerous.

### Features

- Levelling by levelling out unevenness or sloping work surface with a max. 2° incline
- Elevation of the unit drain so that it can go over an overflow edge on the working surface of up to 16 cm
- Can be fixed onto the working surface (welded or screwed onto the working surface with threaded bolts)
- The rubber slide protection included prevents the unit from slipping during operation
- Open on all sides
- Height-adjustable feet
- Mounting kit for fixing the cooking system on the base frame

### Technical specifications

Max. fixed power:	270 kg
Feet height-adjustable up to:	50 mm

### Dimensions and weights

Width (W):	629 mm
Height (H):	148 mm
Depth (D):	438 mm
Weight:	4,5 kg

### Material

Rust-free stainless steel (CNS 1.4301/AISI 304)

### Note

USPH requires that the stand be freely accessible from two opposite sides for cleaning purposes. If this is not possible, a ground clearance of at least 200 mm is specified.

## Datasheets

## Stand XS model XS 6 2/3

