

Jolly Tiered Display

For general purpose or fresh meat display

SLX14

SL10



FEATURES

SL model - White laminated exterior & interior

SLX model - Stainless steel exterior & interior

M model is suitable for fresh meat

4 shelves (able to tilt) with ticket strip & shelf edge stopper

Night blind as standard

Internal illumination

Tempered glass side panels

Castors standard

TECHNICAL SPECIFICATIONS

Controller: Digital controller with temperature display

Cooling: Ventilated

Defrost: Automatic

Refrigerant: R507

Climate Class 3

Power Supply: 13amp

MODEL	FINISH	GROSS CAPACITY	TEMPERATURE RANGE	EXT. DIMENSIONS (H x W x D mm)	POWER CONSUMPTION	WEIGHT (kg)	RRP
SL7	White laminated	438L	+2°C ~ +6°C	2085 x 685 x 737	890W	128	
SL10		657L	+2°C ~ +6°C	2085 x 985 x 737	950W	166	
SL14		913L	+2°C ~ +6°C	2085 x 1335 x 737	1200W	181	
SL19		1314L	+2°C ~ +6°C	2085 x 1885 x 737	1550W	257	
SLX7	Stainless steel	438L	+2°C ~ +6°C	2085 x 685 x 737	890W	128	
SLX10		657L	+2°C ~ +6°C	2085 x 985 x 737	950W	166	
SLX14		913L	+2°C ~ +6°C	2085 x 1335 x 737	1200W	181	
SLX19		1314L	+2°C ~ +6°C	2085 x 1885 x 737	1550W	257	
SL7M	White laminated	438L	0°C ~ +2°C	2085 x 685 x 737	1240W	128	
SL10M		657L	0°C ~ +2°C	2085 x 985 x 737	1300W	166	
SL14M		913L	0°C ~ +2°C	2085 x 1335 x 737	1375W	181	
SL19M		1314L	0°C ~ +2°C	2085 x 1885 x 737	1830W	257	
SLX7M	Stainless steel	438L	0°C ~ +2°C	2085 x 685 x 737	1240W	128	
SLX10M		657L	0°C ~ +2°C	2085 x 985 x 737	1300W	166	
SLX14M		913L	0°C ~ +2°C	2085 x 1335 x 737	1375W	181	
SLX19M		1314L	0°C ~ +2°C	2085 x 1885 x 737	1830W	257	



1
YEAR
WARRANTY



M model is suitable for fresh meat storage

Mondial
Elite