



The Refrigeration Experts

Product specification



EP700M: 600 Ltr Cabinet Refrigerator

41-110

Single door meat storage cabinet

About the product

With EcoPro G3 Cabinets you get the best of both worlds: high performance coupled with low energy consumption, from the Refrigeration Experts.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#) options

Learn more about our [EcoPro G3 range](#)

Why choose this product

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Operates in ambient temperatures of up to 43°C

Specification

Technical

Temperature	Meat -2/+2°C
Thermal heat rejection (W)	270
Electrical supply	230/50/1
Current (A)	2.5
Power (W)	270
Refrigerant mass (g)	80
Refrigerant	R290

Dimensions

Height (mm)	2080
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	600
Net volume	479.9
GN size	2/1
Gross weight (kg)	115.5
Net weight (kg)	105.5

Build

Cabinet type	Standard
Door material	304 Stainless steel
Finish ext/int	S/S & S/S
Section configuration	
System	Integral
Leg type	Braked castors

Energy

Climate Class	5
Energy grade	B
EEI	30.22
AEC (kWh)	1161
GWP	3
Energy consumption (kWh/24hr)	3.18

Footnotes

- Castors are not available if product is supplied less condensing unit
- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.