

Galaxy+ GP10 Black

Multideck

Product Features

- Fully automatic, fan assisted cooling
- Horizontal LED lighting
- Solid 40 mm endwalls with mirrored interior
- Soft closing nightblind
- Adjustable shelves, max weight 160kg/sq metre
- \bullet Shelves can be flat or angled to 7° or 14°
- EPOS Ticket strips & shelf risers
- Suitable for fresh meat
- Can be multiplexed with kit (POA)

Open front multideck

The TEFCOLD Galaxy+ open front is our latest innovation in plugin multidecks. We've combined an expanded display area and optimised cabinet efficiency that provides easy access to customers for impulse buys with excellent LED lighting. The cabinets come with 39mm EPOS ticket strips together with shelf risers as standard. The 5 Shelves can be angled at 7 or 15 degrees to give more options for merchandising and creating an attractive display for your customers. The Galaxy+ open range is suitable for fresh meat, dairy and drinks. It is ideal for use in supermarkets, convenience stores, farm shops, delis and sandwich shops.

| Measures and Content | | |
|----------------------------|----------|-------------------|
| Total Display Area | m² | 1.44 |
| Temperature Range | °C | -1 to +5 |
| Climate Class | | 3 |
| Gross / Net Weight | kg | 208 / 196 |
| Gross / Net Volume | 1 | 1083 / 472 |
| Design and Material | | |
| Shelves Number & Type | | 5 adjustable |
| Shelf Color | | Black |
| Shelf Dimensions | | 938x400mm |
| Max load on Shelves | kg/m² | 160 |
| Feet / Legs | | 4 adjustable feet |
| Exterior Finish | | Black RAL9005 |
| Interior Finish | | Black (RAL9005) |
| Interior Light | | LED |
| Lock | | No |
| Cooling and Functions | | |
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 110 |
| Thermometer | | Yes |
| Power and Consumption | | |
| Energy Class | | D |
| Energy Consumption | kWh/24h | 10.83 |
| Annual Energy Consumption | kWh/year | 3953 |
| Power | | 13 Amp |
| Max Ambient | | 25°C at 60% RH |
| Input Power | W | 580 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 55 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | 938 x 544 x 1562 |
| External Dimension (WxDxH) | mm | 1018 x 740 x 2040 |
| Packed Dimension (WxDxH) | mm | 1100 x 770 x 2320 |
| 40ft Container Load | pcs | 30 |
| | | |