

## HOT CUPBOARDS

## REFRIGERATED SALAD WELL WITH GANTRY

MODEL NO: RW30MSG

GN1/1 gastronorm compatible blown air refrigerated mobile salad well. Ideal for general purpose usage in all catering establishments, schools & colleges, residential care homes, pubs, hotels and cafes.



### DIMENSIONS

External: 1205mm x 650mm x 900mm  
Well: 975mm x 530mm x 170mm

### ELECTRICAL CONNECTIONS

220V/240V; 1 phase 50Hz, 1.6kW loading,  
Cable: 2 metres with 13 amp plug fitted

### REFRIGERANT

R452a - zero ODP and low GWP refrigerant

### CONSTRUCTION

Top: Stainless steel  
Exterior: Stainless steel  
Interior: Stainless steel

### CAPACITY

3 x GN1/1 x 100mm deep

### OPERATING CONDITIONS

Designed to comply with the operating requirements of EN ISO 23953 - 2:2005.  
Performance level M1 (-1°C to +5°C) in Climate class 3 (25°C 60% RH 0.2m/s).  
In use these units will maintain the core product temperature of pre-chilled food below 5°C in ambient temperatures up to 27°C - 50% Relative Humidity

### PRODUCT FEATURES

- L.E.D. illuminated gantry with toughened curved glass sneeze screen/over shelf 304 grade stainless steel well - 170mm deep
- Load line indicator at 100mm to assist in the safe presentation of food
- Accepts GN1/1 gastronorm containers up to 100mm deep
- Completely removable well giving easy access for cleaning and maintenance
- Microprocessor controlled with automatic defrost & condense handling system
- Rear operator's side finished in stainless steel
- Four x 100mm swivel castors two braked

### EXTRAS

- Tray slides
- Push bars
- Corner bumpers
- Height adjustable feet in place of castors



**VICTOR**

TELEPHONE  
01274 722125

EMAIL  
sales@victormfg.co.uk

WEBSITE  
www.victoronline.co.uk