



The Refrigeration Experts

## Product specification

---



### MBCFT75: 75kg Modular Blast Chiller Freezer

17-124

Modular blast chiller/freezer with 700mm door width complete with 25mm floor and integral ramp

#### About the product

High capacity **Modular Blast Chillers** from the Refrigeration Experts allow bulk rapid chilling without compromising food safety or quality.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#).

Learn more about our [Blast Chiller range](#)

## Why choose this product

- 75kg chilling capacity 70°C to 3°C in less than 90 minutes within specifications. Entry temperature of up to 90°C for chilling
- Freezing capacity from 70° to -18°C in less than 240 minutes within specifications
- Supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase+neutral)
- Foster Circulair air circulation system ensures uniform chilling whilst protecting the food surface
- Robust modular construction
- Intuitive easy touch control panel – Just press and go with easy to use colour coding to indicate cycle status
- Operator-friendly fans cut-out whenever the blast chiller door is opened

## Specification

Technical		Dimensions	
<b>Refrigerant</b>	R404a/449a/452a	<b>Height (mm)</b>	2350
<b>Electrical supply</b>	230/50/1	<b>Width (mm)</b>	1350
<b>Fuse rating (A)</b>	20	<b>Depth (mm)</b>	1300
<b>Current (A)</b>	17.5	<b>Gross volume (ltr)</b>	75
<b>Power (W)</b>	4025	<b>Chilling capacity (kg)</b>	75
<b>Refrigeration duty (kW)</b>	8850	<b>Freezing capacity (kg)</b>	75
		<b>Gross weight (kg)</b>	790
		<b>Net weight (kg)</b>	749

Build		Energy	
<b>Finish ext/int</b>	White lam & White foodsafe finish	<b>Climate Class</b>	5
<b>Section configuration</b>	Right hinge	<b>Freezing capacity (kg)</b>	75
<b>System</b>	Remote		

#### Footnotes

- Anti Condensation heater to control panel recommended where products are installed in an ambient below 15°C e.g. Prep rooms
- All models supplied less condensing unit for remote application. Separate electrical supply required for condensing unit (3 phase + neutral)

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.