



The Refrigeration Experts

## Product specification

---



### FFC4/2: 96 Ltr Counter Vari Temp Drawer

35-206

Variable temperature two drawer reduced width counter with splashback

#### About the product

The Foster FlexDrawer offers innovative counter storage solutions for the most demanding professional kitchens.

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [FlexDrawer Counters](#)

## Why choose this product

- Lockable drawers provide maximum security
- Automatic hot gas defrost
- So simple to operate – change drawer temperature from fridge to freezer at the touch of a button
- High quality 304 grade stainless steel finish is food safe and hard wearing
- 100mm 304 grade stainless steel splashback prevents spillage behind the counter
- 2 x GN 1/1 150mm deep pan capacity per drawer maximises available storage space
- Fully removable robust drawer bins allow ease of cleaning
- Robust, heavy duty drawer runners can sustain up to 200kg in weight
- Supplied on roller castors as standard for ease of movement and positioning
- Works in hot kitchens, operating in ambient temperatures up to ISO Climate Class 5
- This is a dual refrigeration system and requires two power supplies. Data about each system can be found in the spec table “Temperature” and “Temperature 2”

# Specification

Technical		Dimensions	
Temperature	Freezer -18/-21°C	Height (mm)	950
Fuse rating (A)	10	Width (mm)	775
Electrical supply	230/50/1	Depth (mm)	720
Power (W)	215	Gross volume (ltr)	48
Refrigerant mass (g)	66	Net volume (ltr)	48
Refrigerant	R290	Leg type	Braked castors
		Gross weight (kg)	138
		Net weight (kg)	130.5

Build		Energy	
Finish ext/int	304 S/S & 304 S/S	Climate Class	5
Section configuration	1/2	Energy grade	B
System	Integral	EEI	26.71
Worktop features	Splashback	AEC (kWh)	710.62
		GWP	3
		Energy consumption (kWh/24hr)	1.95

## Footnotes

- FFC4-2 requires two mains leads
- EcoDesign data relevant per compartment
- Adequate airflow must be kept around the counter: 50mm
- Add 20mm for depth if product is to be wall sited. Stopper required for air circulation – detachable if not wall sited.
- Accepts GN pans with a maximum depth of 150mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.